

SPECIFICATION & FEATURES

ZINC DIE CAST INSULATED STRAIGHT LIQUID TIGHT CONNECTORS

DESCRIPTION:

Orbit Industries' zinc die-cast insulated throat connectors are used with metallic and non-metallic liquid-tight conduit. When flexibility is required for the installation, operation, or maintenance of electrical appliances, type B conduits and fittings are used.



CERTIFICATION:


UL file E310658, Conforms to UL 514B



FEATURES:

- Zinc Die Cast
- With Insulated Throat
- Insulated Color May Vary

LINE DRAWINGS:



CONFIGURATION DATA:

Part No.	Trade Size	A (in)	B (in)	C (in)	Std.Pkg.	Master Ctn.
LTI-38	3/8"	1.496	1.299	0.512	25	250
LTI-50	1/2"	1.496	1.299	0.512	25	250
LTI-75	3/4"	1.516	1.575	0.512	15	150
LTI-100	1"	1.929	1.811	0.650	8	80
LTI-125	1-1/4"	2.067	2.264	0.650	5	50
LTI-150	1-1/2"	2.126	2.520	0.650	4	40
LTI-200	2"	2.028	2.992	0.650	1	36
LTI-250	2-1/2"	3.425	3.740	0.965	1	10
LTI-300	3"	3.563	4.350	0.965	1	10
LTI-350	3-1/2"	4.094	4.862	0.965	1	6
LTI-400	4"	4.154	5.217	0.965	1	6

