

Thermal Transfer Continuous Tapes

- Tapes offer crisp, clear legends with superior legibility
- Conformable material for flat applications and safety and facility identification
- Can be over-laminated to increase durability
- Use thermal transfer resin ribbon

- Temperature ranges:
 Vinyl: -58°F to 176°F (-50°C to 80°C)
 Polyolefin: -40°F to 180°F (-40°C to 82°C)
 Polyester & Super-Tack Polyester: -40°F to 302°F (-40°C to 150°C)
 Reflective: -40°F to 180°F (-40°C to 82°C)



Part Number	Color	Material	Width		Length		Std. Pkg. Qty. (Roll)
			In.	mm	Ft.	m	
T024X000FJT*	White	Polyolefin	0.24	6.1	100.0	30.5	1
T031X000FJT*			0.31	7.9			
T038X000FJT*			0.38	9.7			
T038X000Y01	Black	Super-Tack Polyester	0.50	12.7	100.0	30.5	1
T038X000YP1	White						
T050X000FJT*	Black	Super-Tack Polyester	0.50	12.7	100.0	30.5	1
T050X000Y01							
T050X000YP1	White	Reflective	1.00	25.4	50.0	15.2	1
T100X000RP1	White						
T100X000RU1	Orange						
T100X000RW1	Red						
T100X000RX1	Yellow						
T100X000VP1Y	White	Vinyl	1.00	25.4	100.0	30.5	1
T100X000VQ1Y	Blue						
T100X000VS1Y	Green						
T100X000VU1Y	Orange						
T100X000VW1Y	Red						
T100X000VX1Y	Yellow	Super-Tack Polyester	2.00	50.8	100.0	30.5	1
T100X000VY1Y	Black						
T100X000Y01	Yellow	Polyester	2.00	50.8	100.0	30.5	1
T100X000Y81	Clear						
T100X000YK1	White	Super-Tack Polyester	2.00	50.8	100.0	30.5	1
T100X000YP1	Blue						
T100X000YQ1	Green						
T100X000YS1	Orange						
T100X000YU1	Red						
T100X000YW1	White	Reflective	2.00	50.8	100.0	30.5	1
T200X000RP1	Orange						
T200X000RU1	Red						
T200X000RW1	Yellow						
T200X000RX1	White						
T200X000VP1Y	Blue	Vinyl	2.00	50.8	100.0	30.5	1
T200X000VQ1Y	Brown						
T200X000VR1Y	Green						
T200X000VS1Y	Gray						
T200X000VT1Y	Orange						
T200X000VU1Y	Purple	Super-Tack Polyester	2.00	50.8	100.0	30.5	1
T200X000VV1Y	Red						
T200X000VW1Y	Yellow	Polyester	2.00	50.8	100.0	30.5	1
T200X000VX1Y	Black						
T200X000VY1Y	Yellow	Super-Tack Polyester	2.00	50.8	100.0	30.5	1
T200X000Y01	Clear						
T200X000Y81	Yellow	Polyester	2.00	50.8	100.0	30.5	1
T200X000YK1	Clear						

Order number of rolls required in multiples of Standard Package Quantity.
 *Labels are roll mounted on 3.00" cores; when using the TDP43ME printer and 3.00" cores, the roll stand (TDP43ME-RS) is required.

Continues on next page