

High Intensity Discharge Lamps

Metal Halide Lamps

Watts	Bulb Base	Product Number	Symbols, Footnotes	Ordering Code	ANSI Code	Pkg. Ballast Ref.	Pkg. Qty. Description (401, 407)	LCL (In.)	MOL (In.)	Rated Avg. Life (Hrs.)(351)	Approx. Initial Lumens(352)	Approx. Mean Lumens(353)	CRI	CCT (K)
-------	-----------	----------------	--------------------	---------------	-----------	-------------------	----------------------------------	-----------	-----------	-----------------------------	-----------------------------	--------------------------	-----	---------

Protected Pulse Start Metal Halide "O" Rated Lamps (372, 374, 391)

Open or enclosed luminaires; pulse start metal halide is designed for operation on only specified ANSI compatible ballasts with metal halide pulse ignitors**

250	ED28	EX39	20756-3	■ ★	MP250/BU/PS	M153/	12	G, Clear, Base Up ± 15° Pulse Start	5	8%	14,000	23,000	16,100	62	3800
			Excl.Mog			M138/O									
320	ED37	EX39	13039-3	■ ★	MP320/BU/PS	M154/	6	G, Clear, Base Up ± 15° Pulse Start	7	11½	20,000	29,500	20,650	65	3800
			Excl.Mog			M132/O									
350	ED37	EX39	39101-1	■ ★	MP350/BU/PS	M131/O	6	G, Clear, Base Up ± 15° Pulse Start	7	11½	20,000	34,000	23,800	64	4000
			Excl.Mog												
400	ED37	EX39	13334-8	■ ★	MP400/BU/PS	M155/M128/	6	G, Clear, Base Up ± 15° Pulse Start	7	11½	20,000	40,000	28,000	65	3800
			Excl.Mog			M135/O									
			13335-5	■ ★	MP400/C/BU/PS	M155/M128/	6	G, Coated Base Up ± 15° Pulse Start	—	11½	20,000	36,000	23,400	68	3600
						M135/O									

For the most current product information, go to the e-catalog on www.philips.com
HID symbols and footnotes located on page 84

