

Halogen Lamps

Decorative, Pro PAR20, Pro PAR30S, Pro PAR30L, Pro PAR38 Lamps

Watts	Bulb	Base	Product Symbols, Number Footnotes	Ordering Code	Volts	Pkg. Qty. #	Description	Class Filament	MOL (In.)	Rated Avg. Life (Hrs.)(93)	Approx. MBCP®	Lumens	Life Years (446)	Energy Cost (445)	Color Temp. (K)
Halogen Decorative Boxed (97)													FTC REQUIREMENTS *		
40	G25	Med.	42084-4 ■	40G25/EV/CL	120	12	Clear	C, CC-8	4 ⁷ / ₁₆	2500	—	550	2.3	\$4.82	2800
			42085-1 ■	40G25/EV/W	120	12	White	C, CC-8	4 ⁷ / ₁₆	2500	—	500	2.3	\$4.82	2800
Halogen Pro PAR20 Lamps (82, 86)															
39	PAR20	Med.	42512-4	39PAR20/EVP/SP10	120	15	Spot 10°	C, CC-8	3 ³ / ₈	1100	3840	480	1.0	\$4.70	2900
			42520-7	39PAR20/EVP/FL25	120	15	Flood 25°	C, CC-8	3 ³ / ₈	1100	865	480	1.0	\$4.70	2900
Halogen Pro PAR30S Lamps (82, 86)															
39	PAR30S	Med.	42896-0	39PAR30S/EVP/FL25	120	15	Flood 25°	C, CC-8	3 ⁵ / ₈	1100	1870	500	1.0	\$4.70	2900
53	PAR30S	Med.	42890-4 ©(104)	53PAR30S/EVP/FL25	120	15	Flood 25°	C, CC-8	3 ⁵ / ₈	1100	3100	920	1.0	\$6.38	2860
			42898-6 ©(104)	53PAR30S/EVP/WFL40	120	15	Wide Flood 40°	C, CC-8	3 ⁵ / ₈	1100	1400	920	1.0	\$6.38	2860
Halogen Pro PAR30L Lamps (82, 86)															
39	PAR30L	Med.	42887-0 ©(104)	39PAR30L/EVP/FL25	120	15	Flood 25°	C, CC-8	4 ¹ / ₂	1100	1870	500	1.0	\$4.70	2900
53	PAR30L	Med.	42892-0 ©(104)	53PAR30L/EVP/FL25	120	15	Flood 25°	C, CC-8	4 ¹ / ₂	1100	3100	920	1.0	\$6.38	2860
			42895-2 ©(104)	53PAR30L/EVP/WFL40	120	15	Wide Flood 40°	C, CC-8	4 ¹ / ₂	1100	1400	920	1.0	\$6.38	2860
Halogen Pro PAR38 Lamps (82, 86)															
39	PAR38	Med. Skt.	42884-7	39PAR38/EVP/FL25	120	12	Flood 25°	C, CC-8	5 ⁵ / ₁₆	1100	1900	540	1.0	\$4.70	2900
53	PAR38	Med. Skt.	42885-4 ©(104)	53PAR38/EVP/FL25	120	12	Flood 25°	C, CC-8	5 ⁵ / ₁₆	1100	3250	920	1.0	\$6.38	2860
	DiOptic Reflector														
72	PAR38	Med. Skt.	42894-6 ©(104)	72PAR38/EVP/SP10	120	12	Spot 10°	C, CC-8	5 ⁵ / ₁₆	1100	16,000	1350	1.0	\$8.67	2880
	DiOptic Reflector		42893-8 ©(104)	72PAR38/EVP/FL25	120	12	Flood 25°	C, CC-8	5 ⁵ / ₁₆	1100	4500	1350	1.0	\$8.67	2880

For the most current product information, go to the e-catalog on www.philips.com.
Halogen symbols and footnotes located on page 106.

