

Safety relays PNOZsigma PNOZ s9

Technical details

| General | 750109 | 751109 | 751189 |
|---|---|---|---|
| Approvals | CCC, CE, EAC (Eurasian), KOSHA, TÜV, cULus Listed | CCC, CE, EAC (Eurasian), KOSHA, TÜV, cULus Listed | CCC, CE, EAC (Eurasian), KOSHA, TÜV, cULus Listed |
| Electrical data | 750109 | 751109 | 751189 |
| Supply voltage | | | |
| Voltage | 24 V | 24 V | 24 V |
| Kind | DC | DC | DC |
| Voltage tolerance | -20 %/+20 % | -20 %/+20 % | -20 %/+20 % |
| Output of external power supply (DC) | 2 W | 2 W | 2 W |
| Residual ripple DC | 20 % | 20 % | 20 % |
| Duty cycle | 100 % | 100 % | 100 % |
| Max. inrush current impulse | | | |
| Current pulse, A1 | 0,7 A | 0,7 A | 0,7 A |
| Pulse duration, A1 | 10 ms | 10 ms | 10 ms |
| Max. overall cable resistance R _{lmax} | | | |
| Feedback loop | 30 Ohm | 30 Ohm | 30 Ohm |
| A1/A2 | 20 Ohm | 20 Ohm | 20 Ohm |
| Inputs | 750109 | 751109 | 751189 |
| Voltage at | | | |
| Feedback loop DC | 24 V | 24 V | 24 V |
| Current at | | | |
| Input circuit DC | 15 mA | 15 mA | 15 mA |
| Feedback loop DC | 15 mA | 15 mA | 15 mA |
| Max. inrush current impulse | | | |
| Current pulse, input circuit | 0,1 A | 0,1 A | 0,1 A |
| Pulse duration, input circuit | 20 µs | 20 µs | 20 µs |
| Current pulse, feedback loop | 0,1 A | 0,1 A | 0,1 A |
| Pulse duration, feedback loop | 20 µs | 20 µs | 20 µs |
| Max. overall cable resistance R _{lmax} | | | |
| Single-channel at UB DC | 30 Ohm | 30 Ohm | 30 Ohm |

Safety relays PNOZsigma PNOZ s9

| Relay outputs | 750109 | 751109 | 751189 |
|--|--------------|--------------|--------------|
| Number of output contacts | | | |
| Safety contacts (N/O), delayed | 3 | 3 | 3 |
| Auxiliary contacts (N/C), delayed | 1 | 1 | 1 |
| Max. short circuit current IK | 1 kA | 1 kA | 1 kA |
| Utilisation category | | | |
| In accordance with the standard | EN 60947-4-1 | EN 60947-4-1 | EN 60947-4-1 |
| Utilisation category of safety contacts | | | |
| AC1 at | 240 V | 240 V | 240 V |
| Min. current | 0,01 A | 0,01 A | 0,01 A |
| Max. current | 6 A | 6 A | 6 A |
| Max. power | 1500 VA | 1500 VA | 1500 VA |
| DC1 at | 24 V | 24 V | 24 V |
| Min. current | 0,01 A | 0,01 A | 0,01 A |
| Max. current | 6 A | 6 A | 6 A |
| Max. power | 150 W | 150 W | 150 W |
| Utilisation category of auxiliary contacts | | | |
| AC1 at | 240 V | 240 V | 240 V |
| Min. current | 0,01 A | 0,01 A | 0,01 A |
| Max. current | 6 A | 6 A | 6 A |
| Max. power | 1500 VA | 1500 VA | 1500 VA |
| DC1 at | 24 V | 24 V | 24 V |
| Min. current | 0,01 A | 0,01 A | 0,01 A |
| Max. current | 6 A | 6 A | 6 A |
| Max. power | 150 W | 150 W | 150 W |
| Utilisation category | | | |
| In accordance with the standard | EN 60947-5-1 | EN 60947-5-1 | EN 60947-5-1 |
| Utilisation category of safety contacts | | | |
| AC15 at | 230 V | 230 V | 230 V |
| Max. current | 5 A | 5 A | 5 A |
| DC13 (6 cycles/min) at | 24 V | 24 V | 24 V |
| Max. current | 5 A | 5 A | 5 A |

Safety relays PNOZsigma PNOZ s9

| Relay outputs | 750109 | 751109 | 751189 |
|--|--------------------------------------|--------------------------------------|--------------------------------------|
| Utilisation category of auxiliary contacts | | | |
| AC15 at | 230 V | 230 V | 230 V |
| Max. current | 5 A | 5 A | 5 A |
| DC13 (6 cycles/min) at | 24 V | 24 V | 24 V |
| Max. current | 5 A | 5 A | 5 A |
| Utilisation category in accordance with UL | | | |
| Voltage | 240 V AC G.U. (same polarity) | 240 V AC G.U. (same polarity) | 240 V AC G.U. (same polarity) |
| With current | 6 A | 6 A | 6 A |
| Voltage | 24 V DC G. U. | 24 V DC G. U. | 24 V DC G. U. |
| With current | 6 A | 6 A | 6 A |
| External contact fuse protection, safety contacts | | | |
| In accordance with the standard | EN 60947-5-1 | EN 60947-5-1 | EN 60947-5-1 |
| Max. melting integral | 260 A²s | 260 A²s | 260 A²s |
| Blow-out fuse, quick | 10 A | 10 A | 10 A |
| Blow-out fuse, slow | 6 A | 6 A | 6 A |
| Blow-out fuse, gG | 10 A | 10 A | 10 A |
| Circuit breaker 24V AC/DC, characteristic B/C | 6 A | 6 A | 6 A |
| External contact fuse protection, auxiliary contacts | | | |
| Max. melting integral | 160 A²s | 160 A²s | 160 A²s |
| Blow-out fuse, quick | 10 A | 10 A | 10 A |
| Blow-out fuse, slow | 6 A | 6 A | 6 A |
| Blow-out fuse, gG | 6 A | 6 A | 6 A |
| Circuit breaker 24 V AC/DC, characteristic B/C | 6 A | 6 A | 6 A |
| Conventional thermal current | 6 A | 6 A | 6 A |
| Contact material | AgCuNi + 0,2 µm Au | AgCuNi + 0,2 µm Au | AgCuNi + 0,2 µm Au |
| Times | 750109 | 751109 | 751189 |
| Switch-on delay | | | |
| With manual start typ. | 60 ms | 60 ms | 60 ms |
| With manual start max. | 80 ms | 80 ms | 80 ms |
| Delay-on de-energisation | | | |
| With E-STOP typ. | 40 ms | 40 ms | 40 ms |
| With E-STOP max. | 50 ms | 50 ms | 50 ms |

Safety relays PNOZsigma PNOZ s9

| Times | 750109 | 751109 | 751189 |
|---|---|---|---|
| Recovery time at max. switching frequency 1/s | | | |
| After power failure | 800 ms | 800 ms | 800 ms |
| Delay time t_v | 0,04 s, 0,1 s, 0,2 s, 0,3 s, 0,4 s, 0,5 s, 0,6 s, 0,7 s, 0,8 s, 1 s, 1,5 s, 2 s, 2,5 s, 3 s, 3,5 s, 4 s, 5 s, 6 s, 7 s, 8 s, 10 s, 12 s, 14 s, 15 s, 16 s, 20 s, 25 s, 30 s, 35 s, 40 s, 50 s, 60 s, 70 s, 80 s, 90 s, 100 s, 120 s, 140 s, 150 s, 160 s, 180 s, 200 s, 210 s, 240 s, 300 s | 0,04 s, 0,1 s, 0,2 s, 0,3 s, 0,4 s, 0,5 s, 0,6 s, 0,7 s, 0,8 s, 1 s, 1,5 s, 2 s, 2,5 s, 3 s, 3,5 s, 4 s, 5 s, 6 s, 7 s, 8 s, 10 s, 12 s, 14 s, 15 s, 16 s, 20 s, 25 s, 30 s, 35 s, 40 s, 50 s, 60 s, 70 s, 80 s, 90 s, 100 s, 120 s, 140 s, 150 s, 160 s, 180 s, 200 s, 210 s, 240 s, 300 s | 0,04 s, 0,1 s, 0,2 s, 0,3 s, 0,4 s, 0,5 s, 0,6 s, 0,7 s, 0,8 s, 1 s, 1,5 s, 2 s, 2,5 s, 3 s, 3,5 s, 4 s, 5 s, 6 s, 7 s, 8 s, 10 s, 12 s, 14 s, 15 s, 16 s, 20 s, 25 s, 30 s, 35 s, 40 s, 50 s, 60 s, 70 s, 80 s, 90 s, 100 s, 120 s, 140 s, 150 s, 160 s, 180 s, 200 s, 210 s, 240 s, 300 s |
| Time accuracy | +/-1 % + +/-20 ms | +/-1 % + +/-20 ms | +/-1 % + +/-20 ms |
| Repetition accuracy | +/-1 % + +/-20 ms | +/-1 % + +/-20 ms | +/-1 % + +/-20 ms |
| Repetition accuracy in the event of an error | +/-15 % + +/-20 ms | +/-15 % + +/-20 ms | +/-15 % + +/-20 ms |
| Min. delay time (operating mode delay-on energisation) | $t_v - 15 \% - 20 \text{ ms}$ | $t_v - 15 \% - 20 \text{ ms}$ | $t_v - 15 \% - 20 \text{ ms}$ |
| Max. delay time | $t_v + 15 \% + 20 \text{ ms}$ | $t_v + 15 \% + 20 \text{ ms}$ | $t_v + 15 \% + 20 \text{ ms}$ |
| Supply interruption before de-energisation in the input circuit | 10 ms | 10 ms | 10 ms |
| Supply interruption before de-energisation | 10 ms | 10 ms | 10 ms |
| Environmental data | 750109 | 751109 | 751189 |
| Climatic suitability | EN 60068-2-78 | EN 60068-2-78 | EN 60068-2-78 |
| Ambient temperature | | | |
| Temperature range | -15 - 55 °C | -15 - 55 °C | -15 - 55 °C |
| Storage temperature | | | |
| Temperature range | -40 - 85 °C | -40 - 85 °C | -40 - 85 °C |
| Climatic suitability | | | |
| Humidity | 93 % r. h. at 40 °C | 93 % r. h. at 40 °C | 93 % r. h. at 40 °C |
| Condensation during operation | Not permitted | Not permitted | Not permitted |
| EMC | EN 60947-5-1, EN 61000-6-2, EN 61000-6-4, EN 61326-3-1 | EN 60947-5-1, EN 61000-6-2, EN 61000-6-4, EN 61326-3-1 | EN 60947-5-1, EN 61000-6-2, EN 61000-6-4, EN 61326-3-1 |
| Vibration | | | |
| In accordance with the standard | EN 60068-2-6 | EN 60068-2-6 | EN 60068-2-6 |
| Frequency | 10 - 55 Hz | 10 - 55 Hz | 10 - 55 Hz |
| Amplitude | 0,35 mm | 0,35 mm | 0,35 mm |

Safety relays PNOZsigma PNOZ s9

| Environmental data | 750109 | 751109 | 751189 |
|---|---|--|--|
| Airgap creepage | | | |
| In accordance with the standard | EN 60947-1 | EN 60947-1 | EN 60947-1 |
| Overvoltage category | III | III | III |
| Pollution degree | 2 | 2 | 2 |
| Rated insulation voltage | 250 V | 250 V | 250 V |
| Rated impulse withstand voltage | 6 kV | 6 kV | 6 kV |
| Protection type | | | |
| Mounting area (e.g. control cabinet) | IP54 | IP54 | IP54 |
| Housing | IP40 | IP40 | IP40 |
| Terminals | IP 20 | IP 20 | IP 20 |
| Mechanical data | 750109 | 751109 | 751189 |
| Mounting position | Any | Any | Any |
| Mechanical life | 10,000,000 cycles | 10,000,000 cycles | 10,000,000 cycles |
| Material | | | |
| Bottom | PC | PC | PC |
| Front | PC | PC | PC |
| Top | PC | PC | PC |
| Connection type | Screw terminal | Spring-loaded terminal | Spring-loaded terminal |
| Mounting type | plug-in | plug-in | plug-in |
| Conductor cross section with screw terminals | | | |
| 1 core flexible | 0,25 - 2,5 mm², 24 - 12 AWG | – | – |
| 2 core with the same cross section, flexible with crimp connectors, no plastic sleeve | 0,25 - 1 mm², 24 - 16 AWG | – | – |
| 2 core with the same cross section, flexible without crimp connectors or with TWIN crimp connectors | 0,2 - 1,5 mm², 24 - 16 AWG | – | – |
| Torque setting with screw terminals | 0,5 Nm | – | – |
| Conductor cross section with spring-loaded terminals: Flexible with/without crimp connector | – | 0,2 - 2,5 mm², 24 - 12 AWG | 0,2 - 2,5 mm², 24 - 12 AWG |
| Spring-loaded terminals: Terminal points per connection | – | 2 | 2 |

Safety relays PNOZsigma PNOZ s9

| Mechanical data | 750109 | 751109 | 751189 |
|---|---------|---------|---------|
| Stripping length with spring-loaded terminals | – | 9 mm | 9 mm |
| Dimensions | | | |
| Height | 98 mm | 100 mm | 100 mm |
| Width | 17,5 mm | 17,5 mm | 17,5 mm |
| Depth | 120 mm | 120 mm | 120 mm |
| Weight | 175 g | 175 g | 175 g |

Where standards are undated, the 2014-07 latest editions shall apply.

Safety characteristic data

| Operating Mode | EN ISO 13849-1: 2015 | EN ISO 13849-1: 2015 | EN 62061 SIL CL | EN 62061 PFH _D [1/h] | IEC 61511 SIL | IEC 61511 PFD | EN ISO 13849-1: 2015 T _M [year] |
|--------------------------|----------------------|----------------------|-----------------|---------------------------------|---------------|---------------|--|
| | PL | Category | | | | | |
| Safety contacts, delayed | PL e | Cat. 4 | SIL CL 3 | 2,34E-09 | SIL 3 | 2,75E-05 | 20 |

All the units used within a safety function must be considered when calculating the safety characteristic data.

Supplementary data

The PFH value depends on the switching frequency and the load on the relay output. If the service life graphs are not accessible, the stated PFH value can be used irrespective of the switching frequency and the load, as the PFH value already considers the relay's B10d value as well as the failure rates of the other components.