



Flexible Conduits & Fittings

T&B Catalog Number:

BVNDZ-M207GT

UPC Number:

78620995167

Status:

Active

Description:

PMAFIX straight black strain relief connector, material - polyamide 6, thread size - M20 x 1.5. conduit size NW - 17, terminal range - 10.0 - 14.0.

Application

In machine and plant construction

For separation of damp and dry areas

Characteristics

Very high impact resistance

Easy installation, simply push the conduit in

High conduit pull-out strength

Very good chemical properties

Free from halogens and cadmium

Integrated strain relief optimally holds and seals cables

If several conductors are used with the connectors multiple sealing inserts should be considered

Fits both conduit profiles - Fine (T) and coarse (G)

General

Material Polyamide 6

Color Black

Thread Type Metric

Compatible With PMAFLEX

Dimension Information

Fits to Conduit Size (NW) 17

Fits to Conduit Size (metric) 20

Fits to Conduit Size (inches) 1/2

Thread Size (Metric) M20 x 1.5

Terminal Range 10.0 - 14.0

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C

Temperature-Short-Term (Celsius) +160 degree C

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

IP Ratings

IP Rating IP66 stat. / IP54 dyn.

Packaging

T&B Inner Pack 50

Package in Units 250

T&B Sold in UOM Each

T&B Weight Per UOM 0.05 lbs. Each

Application Support

PMA Reference Guide Available on Website

Product Overview-PMAFIX Connectors Available on Website

PMAFIX Connectors-Safety and Sealing Systems Available on Website

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com