## Thomas@Betts



Family

 Catalog Number:
 SUWV-N043-UL

 Product ID:
 7TAA292460R0073

 UPC Number:
 78620997199

 EAN Number:
 07630030277443

Status: Active

FIXPlus 90 Degree Grey Elbow, Material - Polyamide 6, Thread Type - NPT, Thread Size - 3/4 Inch, Conduit Size NW - 23

- Extremely high impact resistance
- · Vibration resistant connection to PMAFLEX conduits
- · Easy installation
- · High conduit pull-out strength
- · Very good chemical properties
- Free from halogens and cadmium
- Fits conduit profile coarse (G)
- Excellent fire characteristics allow application in public buildings such as hospitals, hotels, airports, train and subway stations, shopping centers, etc.

| North American Specifications (UNSPSC) |   |  |
|--|---|--|
| UNSPSC                                 | 39131707 Electrical conduit coupling            |  |
| IGCC                                   | 5548 Electrical conduit coupling                |  |
| Brand Name                             | PMA   |  |
| Туре                                   | Elbows-90 Degree                                |  |
| Special Features                       | Elbows-90 Degree                                |  |
| Application                            | For Cable Protection Systems In a Wide Range of |  |
|  | Applications                                    |  |
| Standard                               | cULus E174370                                   |  |
| Material                               | Polyamide/Nylon 6                               |  |

| ETIM  | EC001176 Screw connection for corrugated plastic |
|---|--|
|   | hose   |
| Nominal diameter  | 25mm   |
| Degree of protection (IP)                                       | IP68   |
| Model   | 90°-elbow  |
| Revolving thread  | N  |
| Construction type   | Internal thread                                  |
| Type of connection  | Snap connection                                  |
| Thread type   | NPT  |
| Thread connection size  | Other  |
| Thread material   | Polyamide  |
| Thread length   | 14mm   |
| Total length  | 56mm   |
| Total height  | 66.5mm   |
| Material  | Polyamide  |
| Material sealing  | No sealing                                       |
| Colour  | Grey   |
| Approved in combination with protective conduit CSA             | Υ  |
| Approved in combination with protective conduit UR              | Υ  |
| Approved in combination with protective conduit DIN EN 61386-23 | N  |
|   | N  |



Approved in combination with protective conduit Lloyd's Register

Operating temperature

Weight Uom

| Packaging                 |                     |
|---------------------------|---------------------|
| Inner Quantity            | 30                  |
| Outer Quantity            | 120                 |
| Outer Dimensions (inches) | 15.748x11.811x8.661 |

-40 - +105°C

0.07 lbs. Each

## For further technical assistance, please contact us...

**T&B Technical Support** MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com