



T5 HO High Performance Lamps*

Watts	Bulb Type	Base	Satco Product #	Lamp Code	Color	Color Kelvin Temp.	CRI	Avg. Rated Hours	Initial Lumens	Nominal Length Inches	M.O.L. Inches	Ctn.	Notes
24	T5	Mini Bi Pin	S8137	F24T5/830/HO/ENV	Warm White	3000	85	24000	2000	24	22 ³ / ₁₆	40	11, 12, 13
			S6437 ▲	FP24/830/HO/ECO	Warm White	3000	82	30000	1875	24	22 ³ / ₁₆	40	11, 12, 13
			S8138	F24T5/835/HO/ENV	Neutral White	3500	85	24000	2000	24	22 ³ / ₁₆	40	11, 12, 13
			S6438 ▲	FP24/835/HO/ECO	Neutral White	3500	82	30000	1875	24	22 ³ / ₁₆	40	11, 12, 13
			S8139	F24T5/841/HO/ENV	Cool White	4100	85	24000	2000	24	22 ³ / ₁₆	40	11, 12, 13
			S6439 ▲	FP24/841/HO/ECO	Cool White	4100	82	30000	1875	24	22 ³ / ₁₆	40	11, 12, 13
			S8118	F24T5/850/HO/ENV	Natural Light	5000	85	24000	2000	24	22 ³ / ₁₆	40	11, 12, 13
			S8119	F24T5/865/HO/ENV	Daylight	6500	85	24000	2000	24	22 ³ / ₁₆	40	11, 12, 13
39	T5	Mini Bi Pin	S8140	F39T5/830/HO/ENV	Warm White	3000	85	24000	3500	36	34	40	11, 12, 13
			S6440 ▲	FP39/830/HO/ECO	Warm White	3000	82	30000	3300	36	34	40	11, 12, 13
			S8141	F39T5/835/HO/ENV	Neutral White	3500	85	24000	3500	36	34	40	11, 12, 13
			S6441 ▲	FP39/835/HO/ECO	Neutral White	3500	82	30000	3300	36	34	40	11, 12, 13
			S8142	F39T5/841/HO/ENV	Cool White	4100	85	24000	3500	36	34	40	11, 12, 13
			S6442 ▲	FP39/841/HO/ECO	Cool White	4100	82	30000	3300	36	34	40	11, 12, 13
			S8120	F39T5/850/HO/ENV	Natural Light	5000	85	24000	3500	36	34	40	11, 12, 13
			S8121	F39T5/865/HO/ENV	Daylight	6500	85	24000	3500	36	34	40	11, 12, 13
54	T5	Mini Bi Pin	S8143	F54T5/830/HO/ENV	Warm White	3000	85	24000	5000	48	45 ¹³ / ₁₆	40	11, 12, 13
			S6443 ▲	FP54/830/HO/ECO	Warm White	3000	82	40000	4725	48	45 ¹³ / ₁₆	40	11, 12, 13
			S8144	F54T5/835/HO/ENV	Neutral White	3500	85	24000	5000	48	45 ¹³ / ₁₆	40	11, 12, 13
			S6444 ▲	FP54/835/HO/ECO	Neutral White	3500	82	40000	4725	48	45 ¹³ / ₁₆	40	11, 12, 13
			S8145	F54T5/841/HO/ENV	Cool White	4100	85	24000	5000	48	45 ¹³ / ₁₆	40	11, 12, 13
			S6445 ▲	FP54/841/HO/ECO	Cool White	4100	82	40000	4725	48	45 ¹³ / ₁₆	40	11, 12, 13
			S8122	F54T5/850/HO/ENV	Natural Light	5000	85	24000	5000	48	45 ¹³ / ₁₆	40	11, 12, 13
			S8123	F54T5/865/HO/ENV	Daylight	6500	85	24000	5000	48	45 ¹³ / ₁₆	40	11, 12, 13
80	T5	Mini Bi Pin	S6446 ▲	FP80/830/HO/ECO	Warm White	3000	82	25000	6575	60	57 ⁹ / ₁₆	40	11, 12, 13
			S6447 ▲	FP80/835/HO/ECO	Neutral White	3500	82	25000	6575	60	57 ⁹ / ₁₆	40	11, 12, 13
			S6448 ▲	FP80/841/HO/ECO	Cool White	4100	82	25000	6575	60	57 ⁹ / ₁₆	40	11, 12, 13

* Shatter Proof is available on all Fluorescent Lamps.