

Heavy Duty Safety Switches Type 4/4X & 12 with Viewing Window

Selection

Description

30–600A, 3-pole 600V max. in fusible and non-fusible versions in Type 4/4X stainless steel and Type 12 enclosures.

All allow viewing of visible blade position. 30–200A also allow viewing of indicating type fuses.

Features

- Rugged installer-friendly enclosure design features a gasket flange with continuously welded seams.
- Tool-free cover latches.
- Two, three and four point mounting.
- Metal handle with large insulating grip features a positive stop in both ON and OFF position.
- Ground lugs provided as standard.
- Type 12 enclosures are fabricated from galvanized steel and are also rated for 3R/3S outdoor applications.
- Type 4X stainless steel switches (30–200A) are provided with stainless steel interior parts.
- The widest range of accessories available including 200% neutrals, gold plated PLC auxiliary contacts and isolated ground kits.



System	Ampere Rating	Catalog Number	List Price \$	Ship. Weight ^①	Maximum Horsepower Ratings ^③					
					240V AC		480V AC	600V AC	250V DC	600V DC
					1 Phase, 2 Wire	3 Phase, 3 Wire	3 Phase, 3 Wire	3-Phase, 3 Wire		

3-Pole, 3 Wire Fusible, Type 12^⑤

600 Volt AC / 250 Volt DC^{②④}

	30	HF361JW		17	3	7 1/2	15	20	5	—
	60	HF362JW		22	10	15	30	50	10	25
	100	HF363JW		26	15	30	60	75	20	25
	200	HF364JW		53	—	60	125	150	40	50
	400	HF365JW		166	—	125	250	350	50	—
	600	HF366JW		168	—	200	400	500	50	—

3-Pole, 3 Wire Non-Fusible, Type 12^⑤

600 Volt AC / 250 Volt DC^{②④}

	30	HNF361JW		14	3	10	20	30	5	—
	60	HNF362JW		21	10	20	50	60	10	25
	100	HNF363JW		25	15	40	75	100	20	25
	200	HNF364JW		51	15	60	125	150	40	50
	400	HNF365JW		133	15	125	250	350	50	—

3-Pole, 3 Wire Fusible, Type 4X Stainless Steel^⑤

600 Volt AC / 250 Volt DC^②

	30	HF361SW		17	3	7 1/2	15	20	5	—
	60	HF362SW		23	10	15	30	50	10	25
	100	HF363SW		28	15	30	60	75	20	25
	200	HF364SW		55	—	60	125	150	40	50
	400	HF365SW		168	15	125	250	350	50	—

3-Pole, 3 Wire Non-Fusible, Type 4X Stainless Steel^⑤

600 Volt AC / 250 Volt DC^②

	30	HNF361SW		15	3	10	20	30	5	—
	60	HNF362SW		23	10	20	50	60	10	25
	100	HNF363SW		27	15	40	75	100	20	25
	200	HNF364SW		54	15	60	125	150	40	50
	400	HNF365SW		134	15	125	250	350	50	—

① In pounds (lbs).

② 60-200A switches are also rated 600V DC.

③ Maximum HP ratings listed apply only when time delay fuses are used.

④ Also rated 3S/3R for outdoor use.

⑤ All switches are suitable for use as service entrance equipment. Use outside poles of 3-pole switch for 2-pole application.