

AUXILIARY SWITCH BLOCK, 1 NC, DIN EN50005, SCREW CONNECTION, FOR CONTACTORS FOR SWITCHING MOTORS, 1-POLE



Figure similar

| General technical data: | | |
|---|----|--|
| product brand name | | SIRIUS |
| Suitability for use | | Contactor relay and power contactor |
| Protection class IP on the front | | IP20 |
| Ambient temperature | | |
| • during storage | °C | -55 ... +80 |
| • during operation | °C | -25 ... +60 |
| Mechanical service life (switching cycles) typical | | 10 000 000 |
| Electrical endurance (switching cycles) at AC-15 at 230 V typical | | 200 000 |
| Contact reliability | | one incorrect switching operation of 100 million switching operations (17 V, 5 mA) |
| Contact reliability of the auxiliary contacts | | 1 faulty switching per 100 million (17 V, 1 mA) |
| Insulation voltage with degree of pollution 3 Rated value | V | 690 |
| Surge voltage resistance Rated value | kV | 6 |
| Auxiliary circuit: | | |
| Number of NC contacts for auxiliary contacts | | |
| • instantaneous contact | | 1 |

| | | |
|---|---|------|
| Number of NO contacts for auxiliary contacts | | |
| • instantaneous contact | | 0 |
| Operating current of the auxiliary contacts at AC-12 | | |
| • at 24 V | A | 10 |
| • at 230 V | A | 10 |
| • maximum | A | 10 |
| Operating current | | |
| • of the auxiliary contacts | | |
| — at AC-14 | | |
| — at 125 V | A | 6 |
| — at 250 V | A | 6 |
| — at AC-15 | | |
| — at 24 V | A | 6 |
| — at 230 V | A | 6 |
| — at 400 V | A | 3 |
| • at AC-15 at 690 V Rated value | A | 1 |
| Operating current | | |
| • with 2 current paths in series at DC-12 | | |
| — at 24 V Rated value | A | 10 |
| — at 60 V Rated value | A | 10 |
| — at 110 V Rated value | A | 4 |
| — at 220 V Rated value | A | 2 |
| — at 440 V Rated value | A | 1.3 |
| — at 600 V Rated value | A | 0.65 |
| • with 3 current paths in series at DC-12 | | |
| — at 24 V Rated value | A | 10 |
| — at 60 V Rated value | A | 10 |
| — at 110 V Rated value | A | 10 |
| — at 220 V Rated value | A | 3.6 |
| — at 440 V Rated value | A | 2.5 |
| — at 600 V Rated value | A | 1.8 |
| Operating current | | |
| • of the auxiliary contacts at DC-13 | | |
| — at 24 V | A | 6 |
| — at 60 V | A | 2 |
| — at 110 V | A | 1 |
| — at 220 V | A | 0.3 |
| • with 2 current paths in series at DC-13 | | |
| — at 24 V Rated value | A | 10 |
| — at 60 V Rated value | A | 3.5 |
| — at 110 V Rated value | A | 1.3 |

| | | |
|---|---|------|
| — at 220 V Rated value | A | 0.9 |
| — at 440 V Rated value | A | 0.2 |
| — at 600 V Rated value | A | 0.1 |
| • with 3 current paths in series at DC-13 | | |
| — at 24 V Rated value | A | 10 |
| — at 60 V Rated value | A | 4.7 |
| — at 110 V Rated value | A | 3 |
| — at 220 V Rated value | A | 1.2 |
| — at 440 V Rated value | A | 0.5 |
| — at 600 V Rated value | A | 0.26 |

Installation/ mounting/ dimensions:

| | | |
|----------------------|----|------------------|
| Mounting type | | snap-on mounting |
| Width | mm | 10 |
| Height | mm | 38 |
| Depth | mm | 51 |

Connections/ Terminals:

| | | |
|--|--|---|
| Type of electrical connection for auxiliary and control current circuit | | screw-type terminals |
| Type of connectable conductor cross-section | | |
| <ul style="list-style-type: none"> • for auxiliary contacts <ul style="list-style-type: none"> — finely stranded — with core end processing • for AWG conductors for auxiliary contacts | | 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) 2x (20 ... 16), 2x (18 ... 14) |

Safety related data:

| | | |
|---|--|-----------|
| Product function Mirror contact acc. to IEC 60947-4-1 | | Yes |
| <ul style="list-style-type: none"> • Note | | with 3RT1 |
| Product function positively driven operation acc. to IEC 60947-5-1 | | No |

Certificates/ approvals:

| | | |
|--------------------------|---------------------------------------|---------------------------|
| General Product Approval | Functional Safety/Safety of Machinery | Declaration of Conformity |
|--------------------------|---------------------------------------|---------------------------|



[Baumusterbescheinigung](#)



| | |
|-------------------|-------------------|
| Test Certificates | Shipping Approval |
|-------------------|-------------------|

[spezielle Prüfbescheinigung](#)

[Typprüfbescheinigung/Werkszeugnis](#)



| | |
|-------------------|-------|
| Shipping Approval | other |
|-------------------|-------|



[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RH19211CA01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RH19211CA01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3RH19211CA01&lang=en

