

Ordering data	Order No.		Order No.
SIWAREX U for SIMATIC S7 and ET 200M, incl. bus connector, weight 0.3 kg <ul style="list-style-type: none"> Single-channel version ^{1) D)} for connecting one scale Two-channel version ^{2) D)} for connecting two scales 	7MH4 950-1AA01 7MH4 950-2AA01	Shield connection terminal Contents: 2 units (suitable for cable with diameter 4 ... 13 mm) Note: one shield connection terminal each is required for: <ul style="list-style-type: none"> Scale connection RS 485 interface RS 232 interface 	6ES7 390-5CA00-0AA0
SIWAREX U manual available in a range of languages Free download on the Internet at: www.siemens.com/weighing-technology		S7 DIN rail 160 mm 480 mm 530 mm 830 mm 2000 mm	6ES7 390-1AB60-0AA0 6ES7 390-1AE80-0AA0 6ES7 390-1AF30-0AA0 6ES7 390-1AJ30-0AA0 6ES7 390-1BC00-0AA0
SIWAREX U configuration package for SIMATIC S7 version 5.4 or higher suitable for 7MH4950-1AA01 and 7MH4950-2AA01 on CD-ROM <ul style="list-style-type: none"> PC SIWATOOL U software (available in a range of languages), new design Sample program "Getting started" – ready to use application for SIMATIC S7 SIWAREX U Manual on CD (in a range of languages), new design HSP Hardware Support Package for integrating SIWAREX U in STEP 7 	7MH4 950-1AK01	Accessories (optional) PS 307 load power supplies (only required if 24 V DC is not available) 120/230 V AC; 24 V DC, incl. power connector PS 307-1B; 2 A PS 307-1E; 5 A PS 307-1K; 10 A	6ES7 307-1BA00-0AA0 6ES7 307-1EA00-0AA0 6ES7 307-1KA00-0AA0
SIWAREX U configuration package for PCS 7, version 6.x suitable for 7MH4601-1*A01 and 7MH4950-*AA01 In German and English on CD-ROM, module for the CFC and faceplate	7MH4 683-3BA64	Labeling strips (10 units, spare part) Remote displays (option) The digital remote displays can be connected directly to SIWAREX U through a TTY interface. The following remote displays can be used: S102, S302 Siebert Industrieelektronik GmbH P.O. Box 1180 D-66565 Eppelborn Tel.: +49 6806/980-0 Fax: +49 6806/980-999 Internet: www.siebert.de Detailed information available from manufacturer.	6ES7 392-2XX00-0AA0
SIWAREX U configuration package for PCS7 S7 version 7.0 and V7.1 suitable for 7MH4950-1AA01 and 7MH4950-2AA01 on CD-ROM <ul style="list-style-type: none"> HSP Hardware Support Package for integration of SIWAREX U in STEP 7 Function block for the CFC chart Faceplate SIWATOOL U setting software Manual 	7MH4 950-3AK61	SIWAREX JB junction box, aluminium housing for connecting up to 4 load cells in parallel, and for connecting several junction boxes	7MH4 710-1BA
SIWATOOL connecting cable D of SIWAREX U/CS with serial PC interface, for 9-pin PC interfaces (RS 232), length 3 m Installation material (mandatory)	7MH4 607-8CA	SIWAREX JB junction box, stainless steel housing for connecting up to 4 load cells in parallel	7MH4 710-1EA
20-pin front plug with screw contacts (required for each SIWAREX module)		Ex interface, type SIWAREX Pi With UL and FM approvals, but without ATEX approval for intrinsically-safe connection of load cells, suitable for the SIWAREX U, CS, MS, FTA, FTC and M weighing modules. Not approved for use in the EU.	7MH4 710-5AA
Shield contact element Sufficient for two SIWAREX U modules	6ES7 392-1AJ00-0AA0		

I: Subject to export regulations AL: N and ECCN: EAR99H