

MOTION CONNECT 800PLUS

MLFB-Ordering data

6FX8002-2DC10-1AC0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Electrical data

Design of the sensor Motor encoder DRIVE-CLiQ

Test voltage, rms Signal conductors 500 V

Rated voltage U0/U in accordance with EN 50395 Power conductors 30 V

Mechanical data

Type of connection cable engine side RJ45 DRIVE-CLiQ

Type of connection cable converter side DRIVE-CLiQ RJ45

Maximum cable outer diameter 7.1 mm

Smallest bending radius (fixed installation) 35 mm

Smallest bending radius (flexible installation) 75 mm

Number of bends, max. 10,000,000

Maximum traversing velocity 300 m/min

Acceleration horizontal, max 50 m/s²

Tensile stress, max. Fixed installation 50 N/mm²

Tensile stress, max. Flexible installation 20 N/mm²

Torsional stress Absolute 30°/m

Length 2.0 m



Figure similar

MLFB-Ordering data

6FX8002-2DC10-1AC0

Technical data

Ambient temperature

Operation with permanently installed cable	-50 ... 80 °C
	Module- and motor-side RJ45 plug -20°C ... 80°C, M17 plug -20 ... 80°C
Operation with moving cable	-20 ... 60 °C
Storage	-20 ... 80 °C
	Module- and motor-side RJ45 plug -20°C ... 80°C, M17 plug -20 ... 80°C

Kind of connection cable

Basis cable

Material of the cable sheath

PUR, HD22.10 S2 (VDE 0282, part 10)
DESINA-color green RAL 6018

Type of insulation

Without CFC and silicone IEC 60754-1/DIN
VDE 0472-815

Standard for behavior in fire: flame resistance

EN 60332-1-1 to 1-3

Oil resistance

EN 60811-2-1

Verification of suitability as authorisation for USA

UL STYLE 2502

Verification of suitability as authorisation for Canada

CSA-N.210.2-M90