

# SIMATIC ET 200 distributed I/O

## ET 200MP

### Interface modules IM 155-5 PN

Ordering data	Order No.	Order No.
<b>IM 155-5 PN interface module</b> IP 20 degree of protection, module width 35 mm, installation on S7-1500 mounting rail	<b>6ES7155-5AA00-0AB0</b>	
<b>Accessories</b> <b>Front flap for IM 155-5 PN (spare part), 5 units</b>	<b>6ES7528-0AA70-7AA</b>	
<b>SIMATIC S7-1500 mounting rail</b> Fixed lengths, with grounding elements <ul style="list-style-type: none"> <li>• 160 mm</li> <li>• 482 mm</li> <li>• 530 mm</li> <li>• 830 mm</li> </ul> For cutting to length by customer, without drill holes; grounding elements must be ordered separately <ul style="list-style-type: none"> <li>• 2000 mm</li> </ul>	<b>6ES7 590-1AB60-0AA0</b> <b>6ES7 590-1AE80-0AA0</b> <b>6ES7 590-1AF30-0AA0</b> <b>6ES7 590-1AJ30-0AA0</b>  <b>6ES7 590-1BC00-0AA0</b>	
<b>PE connection element for mounting rail 2 000 mm</b> 20 units	<b>6ES7 590-5AA00-0AA0</b>	
<b>Power supply</b> For supplying the backplane bus of the S7-1500 24 V DC input voltage, power 25 W 24/48/60 V DC input voltage, power 60 W 120/230 V AC input voltage, power 60 W	<b>6ES7 505-0KA00-0AB0</b> <b>6ES7 505-0RA00-0AB0</b>  <b>6ES7 507-0RA00-0AB0</b>	
<b>Power connector</b> With coding element for power supply module; spare part, 10 units	<b>6ES7 590-8AA00-0AA0</b>	
<b>Load power supply</b> 24 V DC/3 A 24 V DC/8 A	<b>6EP1 332-4BA00</b> <b>6EP1 333-4BA00</b>	
<b>Power supply connector</b> Spare part; for connecting the 24 V DC supply voltage <ul style="list-style-type: none"> <li>• with push-in terminals</li> </ul>	<b>6ES7 193-4JB00-0AA0</b>	
		<b>IE FC RJ45 plugs</b> RJ45 plug connector for Industrial Ethernet with a rugged metal enclosure and integrated insulation displacement contacts for connecting Industrial Ethernet FC installation cables  <b>IE FC RJ45 plug 180</b> 180° cable outlet 1 unit 10 units 50 units
		<b>IE FC TP Standard Cable GP 2x2</b> 4-core, shielded TP installation cable for connection to IE FC Outlet RJ45/ IE FC RJ45 Plug; PROFINET-compatible; with UL approval; Sold by the meter, max. length 1 000 m; minimum order 20 m
		<b>IE FC TP Trailing Cable 2 x 2 (Type C)</b> 4-core, shielded TP installation cable for connection to IE FC Outlet RJ45/ IE FC RJ45 Plug 180/90 for trailing cable use; PROFINET-compatible; with UL approval; Sold by the meter, max. length 1 000 m; minimum order 20 m
		<b>IE FC TP Marine Cable 2 x 2 (Type B)</b> 4-core, shielded TP installation cable for connection to IE FC Outlet RJ45/ IE FC RJ45 Plug 180/90 marine certified, Sold by the meter, max. length 1 000 m; minimum order 20 m
		<b>IE FC Stripping Tool</b> Preadjusted stripping tool for fast stripping of Industrial Ethernet FC cables
		<b>6GK1 901-1BB10-2AA0</b> <b>6GK1 901-1BB10-2AB0</b> <b>6GK1 901-1BB10-2AE0</b>  <b>6XV1 840-2AH10</b>  <b>6XV1 840-3AH10</b>  <b>6XV1 840-4AH10</b>  <b>6GK1 901-1GA00</b>