

**Selection and ordering data**

Description	Article No.
<b>Active Line Module in booksize format</b>	
<b>Internal air cooling</b> Rated power:	
• 16 kW	<b>6SL3130-7TE21-6AA4</b>
• 36 kW	<b>6SL3130-7TE23-6AA3</b>
• 55 kW	<b>6SL3130-7TE25-5AA3</b>
• 80 kW	<b>6SL3130-7TE28-0AA3</b>
• 120 kW	<b>6SL3130-7TE31-2AA3</b>
<b>External air cooling</b> Rated power:	
• 16 kW	<b>6SL3131-7TE21-6AA3</b>
• 36 kW	<b>6SL3131-7TE23-6AA3</b>
• 55 kW	<b>6SL3131-7TE25-5AA3</b>
• 80 kW	<b>6SL3131-7TE28-0AA3</b>
• 120 kW	<b>6SL3131-7TE31-2AA3</b>
<b>Cold plate cooling</b> Rated power:	
• 16 kW	<b>6SL3136-7TE21-6AA3</b>
• 36 kW	<b>6SL3136-7TE23-6AA3</b>
• 55 kW	<b>6SL3136-7TE25-5AA3</b>
• 80 kW	<b>6SL3136-7TE28-0AA3</b>
• 120 kW	<b>6SL3136-7TE31-2AA3</b>
<b>Liquid cooling</b> Rated power:	
• 120 kW	<b>6SL3135-7TE31-2AA3</b>
<b>Accessories for re-ordering</b>	
<b>Accessories pack</b> (plug-in terminals, DRIVE-CLiQ jumper, dust-proof blanking plugs) For DRIVE-CLiQ port	
• For Active Line Modules with a width of 100 mm, int./ext. air cooling	<b>6SL3163-8FD00-0AA0</b>
• For Active Line Modules with a width of 150 mm, int./ext. air cooling	<b>6SL3163-8GF00-0AA0</b>
• For Active Line Modules with a width of 200 mm, int./ext. air cooling	<b>6SL3163-8HH00-0AA0</b>
• For Active Line Modules with a width of 300 mm, int./ext. air cooling	<b>6SL3163-8JM00-0AA0</b>
<b>SINAMICS/SINUMERIK/SIMOTION dust-proof blanking plugs</b> (50 units) For DRIVE-CLiQ port	<b>6SL3066-4CA00-0AA0</b>

Description	Article No.
<b>Accessories</b>	
<b>Shield connection plate</b> For Line Modules and Motor Modules in booksize format	
• 150 mm wide for internal air cooling	<b>6SL3162-1AF00-0AA1</b>
• 150 mm wide for external air cooling and cold plate cooling	<b>6SL3162-1AF00-0BA1</b>
• 200 mm wide for internal air cooling	<b>6SL3162-1AH01-0AA0</b>
• 200 mm wide for external air cooling and cold plate cooling	<b>6SL3162-1AH01-0BA0</b>
• 300 mm wide for all cooling types	<b>6SL3162-1AH00-0AA0</b>
<b>DC link rectifier adapter</b> For direct infeed of DC link voltage	
• Screw-type terminals 0.5 ... 10 mm <sup>2</sup> For Line Modules and Motor Modules in booksize format with a width of 50 mm or 100 mm	<b>6SL3162-2BD00-0AA0</b>
• Screw-type terminals 35 ... 95 mm <sup>2</sup> For Line Modules and Motor Modules in booksize format with a width of 150 mm, 200 mm and 300 mm	<b>6SL3162-2BM00-0AA0</b>
<b>DC link adapter (2 units)</b> For multi-tier configuration Screw-type terminals 35 ... 95 mm <sup>2</sup> For all Line Modules and Motor Modules in booksize format	<b>6SL3162-2BM01-0AA0</b>
<b>24 V terminal adapter</b> For all Line Modules and Motor Modules in booksize format	<b>6SL3162-2AA00-0AA0</b>
<b>24 V jumper</b> For connection of the 24 V busbars (for booksize format)	<b>6SL3162-2AA01-0AA0</b>
<b>Warning labels in 30 languages</b> This set of foreign language warning labels can be placed on top of the standard German or English signs. A set of labels is supplied with the units. One sign in each of the following languages is provided in each set: BG, CN, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, JP, KR, LT, LV, MT, NL, NO, PL, PT, RO, RU, SE, SI, SK, TR	<b>6SL3166-3AB00-0AA0</b>