



Figure similar

MLFB-Ordering data

1PH8163-1DF03-0BA1

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \phi$	I_{μ} [A]
ALM 400V	34.0	186.0	70.0	366	59.2	1750	600	217.0	6500.0	252.0	87	0.926	0.87	24.6
Y BLM/SLM 400V	30.0	191.0	71.0	319	50.8	1500	600	217.0	6500.0	252.0	87	0.923	0.87	25.6
ALM/BLM/SLM 480V	37.0	177.0	68.0	416	67.4	2000	600	217.0	6500.0	252.0	87	0.932	0.86	24.6

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft extension	Plain shaft
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Connection

Type of electrical connection	Terminal box
Terminal box position	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk863

Physical constants

Thermal time constant	35 min
Moment of inertia	0.21600 kgm ²
Weight (approx.)	196 kg

MLFB-Ordering data

1PH8163-1DF03-0BA1



Figure similar

Cooling data and sound pressure level

Airflow, min.	0.16 m ³ /s
---------------	------------------------

Sound pressure level LpA(1m) motor +
external fan operation 50 HZ rated 73 dB *
load, tolerance + 3dB

Air discharge	axial
---------------	-------

Pressure drop	200 Pa
---------------	--------

* at a rated frequency of 4 kHz and a speed range of up to 5000 rpm