

General Application Molded Case Circuit Breakers

Lug-In/Lug-Out with INSTA-WIRE

Selection

All BQ/BQH/HBQ circuit breakers are supplied with load side lugs. If line side lugs are required, add suffix "L" to catalog number. Consult Siemens for any additional charge. All standard circuit breakers are calibrated for 40°C maximum ambient application.

Continuous Current Rating @ 40° C	Type BQ ^①	Type BQH	Type HBQ
	10,000A IR	22,000A IR	65,000A IR
	Catalog Number	Catalog Number	Catalog Number

1-Pole (120V AC)^⑤

15	BQ1B015 ^④	BQ1B015H ^④	HB1B015 ^④
20	BQ1B020 ^④	BQ1B020H ^④	HB1B020 ^④
25	BQ1B025	BQ1B025H	HB1B025
30	BQ1B030	BQ1B030H	HB1B030
35	BQ1B035	BQ1B035H	HB1B035
40	BQ1B040	BQ1B040H	HB1B040
45	BQ1B045	BQ1B045H	HB1B045
50	BQ1B050	BQ1B050H	HB1B050
60	BQ1B060	BQ1B060H	HB1B060
70	BQ1B070	BQ1B070H	HB1B070

2-Pole (Common-Trip 120/240V AC)^④

15	BQ2B015	BQ2B015H	HB2B015
20	BQ2B020	BQ2B020H	HB2B020
25	BQ2B025	BQ2B025H	HB2B025
30	BQ2B030	BQ2B030H	HB2B030
35	BQ2B035	BQ2B035H	HB2B035
40	BQ2B040	BQ2B040H	HB2B040
45	BQ2B045	BQ2B045H	HB2B045
50	BQ2B050	BQ2B050H	HB2B050
60	BQ2B060	BQ2B060H	HB2B060
70	BQ2B070	BQ2B070H	HB2B070
80	BQ2B080	BQ2B080H	HB2B080
90	BQ2B090	BQ2B090H	HB2B090
100	BQ2B100	BQ2B100H	HB2B100
110	BQ2B110	BQ2B110H	HB2B110
125	BQ2B125	BQ2B125H	HB2B125

2-Pole (Common-Trip 240V AC)^{③④}

15	BQ2H015	—	—
20	BQ2H020	—	—
30	BQ2H030	—	—
40	BQ2H040	—	—
50	BQ2H050	—	—
60	BQ2H060	—	—
70	BQ2H070	—	—
80	BQ2H080	—	—
90	BQ2H090	—	—
100	BQ2H100	—	—

3-Pole (Common-Trip 240V AC)^⑦

15	BQ3B015	BQ3B015H	HB3B015
20	BQ3B020	BQ3B020H	HB3B020
25	BQ3B025	BQ3B025H	HB3B025
30	BQ3B030	BQ3B030H	HB3B030
35	BQ3B035	BQ3B035H	HB3B035
40	BQ3B040	BQ3B040H	HB3B040
45	BQ3B045	BQ3B045H	HB3B045
50	BQ3B050	BQ3B050H	HB3B050
60	BQ3B060	BQ3B060H	HB3B060
70	BQ3B070	BQ3B070H	HB3B070
80	BQ3B080	BQ3B080H	HB3B080
90	BQ3B090	BQ3B090H	HB3B090
100	BQ3B100	BQ3B100H	HB3B100


BQ / BQH / HBQ Internal Accessories

Description	Catalog Number	Field/Factory Installed
120V Shunt Trip	add suffix...00S01	Factory
24V Shunt Trip	add suffix...00S07	Factory
120V Auxiliary Switch	add suffix...01	Factory

■ Built to order. Allow 2-3 weeks for delivery
 ① UL Listed for use with 60/75° wire through 40 amps,
 UL listed for use with 75° wire only for 50 amps
 and above, HACR rated.

② 1A and 1B contacts.
 ③ UL Listed for use on 3-phase grounded "B" systems —
 10,000 for this application.
 ④ UL Listed for frequent switching
 applications (SWD). 120V AC Fluorescent Lighting.

⑤ Shipped 12 per sleeve.
 ⑥ Shipped 6 per sleeve.
 ⑦ Shipped 4 per sleeve.
 ⑧ UL Listed 5KA IR.



Factory Modifications

Description	Catalog Number
Line Side Lugs	add suffix...L
Quick Connect Lug	add suffix...QX
400Hz Calibration	add suffix...Y ^⑧
Marine 50° C Ambient Calibration	add suffix...M
Fungus Proofing	add suffix...F

For external accessories, please refer to page 17/106

General Application Molded Case Circuit Breakers

DIN Rail Mounted Circuit Breakers

Selection/Dimensions

Breaker Type	Ampere Rating	Catalog Number	Load Side Connector	Interrupting Ratings (KA) (RMS Symmetrical Amperes) Volts AC	
				120	120/240

1-Pole DIN Rail (120V AC)

BQXD 1-Pole 120V DIN Rail	10	BQ1B010QLD	TC1Q1	10	
	15	BQ1B015QLD	TC1Q1	10	
	20	BQ1B020QLD	TC1Q1	10	
	25	BQ1B025QLD	TC1Q1	10	
	30	BQ1B030QLD	TC1Q1	10	
	35	BQ1B035QLD	TC1Q1	10	
	40	BQ1B040QLD	TC1Q1	10	
	45	BQ1B045QLD	TA1Q1	10	
	50	BQ1B050QLD	TA1Q1	10	
	60	BQ1B060QLD	TA1Q1	10	
	10	BQ1B010QXD	Quick-Connect	10	
	15	BQ1B015QXD	Quick-Connect	10	
	20	BQ1B020QXD	Quick-Connect	10	
	25	BQ1B025QXD	Quick-Connect	10	
	30	BQ1B030QXD	Quick-Connect	10	
	35	BQ1B035QXD	Quick-Connect	10	
	40	BQ1B040QXD	Quick-Connect	10	
	45	BQ1B045QXD	Quick-Connect	10	
	50	BQ1B050QXD	Quick-Connect	10	
	60	BQ1B060QXD	Quick-Connect	10	

2-Pole DIN Rail (120/240V AC)

BQXD 2-Pole 120/240V DIN Rail	10	BQ2B010QLD	TC1Q1		10
	15	BQ2B015QLD	TC1Q1		10
	20	BQ2B020QLD	TC1Q1		10
	25	BQ2B025QLD	TC1Q1		10
	30	BQ2B030QLD	TC1Q1		10
	35	BQ2B035QLD	TC1Q1		10
	40	BQ2B040QLD	TC1Q1		10
	45	BQ2B045QLD	TA1Q1		10
	50	BQ2B050QLD	TA1Q1		10
	60	BQ2B060QLD	TA1Q1		10
	10	BQ2B010QXD	Quick-Connect		10
	15	BQ2B015QXD	Quick-Connect		10
	20	BQ2B020QXD	Quick-Connect		10
	25	BQ2B025QXD	Quick-Connect		10
	30	BQ2B030QXD	Quick-Connect		10
	35	BQ2B035QXD	Quick-Connect		10
	40	BQ2B040QXD	Quick-Connect		10
	45	BQ2B045QXD	Quick-Connect		10
	50	BQ2B050QXD	Quick-Connect		10
	60	BQ2B060QXD	Quick-Connect		10

Lugs-For Use with BQ, BQH, HBQ^④

Circuit Breaker Amp. Rtg.	Cab. Per Lug	Lug Wire Range AWG	Catalog Number
Line Side			
10-40	1	#16-#6 Cu #12-#6 Al	TC1Q1 ^{②③}
45-125	1	#8-#1 Cu #6-#1/0 Al	TA1Q1
Load Side			
10	2	#16 Cu	Connectors are Supplied with Circuit Breaker
15-20	1	#14-#10 Cu #12-#10 Al	
25-35	1	#14-#6 Cu #12-#10 Al	
40-50	1	#8-#6 Cu #8-#4 Al	
55-70	1	#8-#4 Cu #8-#2 Al	
80-100	1	#4-#1/0 Cu #2-#1/0 Al	
110-125	1	#2-#1/0 Cu #1/0-#2/0 Al	

For inches / millimeters conversion, see Application Data section.

■ Built to order. Allow 2-3 weeks for delivery.

① UL Listed for use with 60/75° wire through 40 amps.
UL listed for use with 75° wire only for 50 amps and above, HACR rated.

Finger Safe Terminal Shield

Protects against accidental contact with lugs—1 per lug. Fits line and load end.

Catalog Number	Qty
BQFS2	2
BQFS1K	1000



Enclosures	
Type	Catalog Number ^④
1	EB3100S ^{②③}
3R	WB3100

② Connector has steel construction.

③ Surface mounted indoor. If flush mounting is required, replace suffix "S" in catalog number with suffix "F".

④ Neutral included in enclosure.

⑤ Enclosure will not accept circuit breakers with shunt trips or auxiliary switches installed.



Breaker Type	Amperes	Dimensions (inches)		
		L	D1	D2
BQ, BQH	15-50	3 3/4	2 3/4	3
BQ, BQH	55-125	4	2 3/4	3
HBQ	15-125	4	2 3/4	3
BQXD	15-60	4 1/2	2 3/4	3

⑥ Type BQXD uses TA1Q1 or TC1Q1 lugs on line side of circuit breaker.

For external accessories, please refer to pages 17/106, 17/108 to 17/113