

Charging station for Mobile Panel 277(F) IWLAN with lock for charging and storing the Mobile Panel 277(F) IWLAN charging of 2 additional batteries



General information	
Product type designation	Charging station
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	3.2 A
Power	
Active power input, typ.	77 W
Degree and class of protection	
Degree of protection acc. to EN 60529	IP65
Standards, approvals, certificates	
Certifications	CE, cULus, C-TICK
CE mark	Yes
cULus	Yes

RCM (formerly C-TICK)	Yes
-----------------------	-----

Ambient conditions

Ambient temperature during operation

• Operation (vertical installation)	0 to +40 °C
— For vertical installation, min.	0 °C
— For vertical installation, max.	40 °C

Ambient temperature during storage/transportation

• min.	-20 °C
• max.	60 °C

Relative humidity

• Operation, max.	85 %
-------------------	------

Dimensions

Width	208 mm
Height	333 mm
Depth	75 mm

Weights

Weight (without packaging)	1.1 kg
----------------------------	--------

Other

Usable in the following products

• Product 1	6AV6645-0EB01-0AX1
• Product 2	6AV6645-0EC01-0AX1
• Product 3	6AV6645-0EF01-0AX1
• Product 4	6AV6645-0GB01-0AX1
• Product 5	6AV6645-0GC01-0AX1
• Product 6	6AV6645-0GF01-0AX1
• Product 7	6AV6645-0DD01-0AX1
• Product 8	6AV6645-0DE01-0AX1
• Product 9	6AV6645-0FD01-0AX1
• Product 10	6AV6645-0FE01-0AX1
• Product 11	6AV6645-0DB01-0AX0
• Product 12	6AV6645-0DC01-0AX0
• Product 13	6AV6645-0DD01-0AX0
• Product 14	6AV6645-0DE01-0AX0

last modified: 12/05/2017