

SIMATIC S7-1200, Communication module CM 1241, RS422/485, 9-pole D-sub (socket) supports Freeport



General information

Product type designation CM 1241 RS422/485

Supply voltage

Rated value (DC)	Yes
• 24 V DC	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption, max. 220 mA; From backplane bus 5 V DC

Power loss

Power loss, typ. 1.1 W

Interfaces

Number of interfaces	1
Interface (physical) RS 422/485 (X.27)	Yes

Point-to-point

• Cable length, max.	1 000 m
----------------------	---------

Integrated protocol driver

— Freeport	Yes
— ASCII	Yes; Available as library function
— Modbus	Yes
— Modbus RTU master	Yes
— MODBUS RTU slave	Yes
— USS	Yes; Available as library function

Protocols

Integrated protocols

Freeport

— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 (Standard), 2
— Parity	No parity (standard); even, uneven, mark (parity bit always 1); space (parity bit always 0)

3964 (R)

— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 (Standard), 2
— Parity	No parity (standard); even, uneven, mark (parity bit always 1); space (parity bit always 0)

Modbus RTU master

— Address area	1 through 49 999 (Standard Modbus addressing)
— Number of slaves, max.	247; slave numbers 1 through 247, per MODBUS network segment maximum 32 devices, additional repeaters needed to expand the network to maximum configuration

MODBUS RTU slave

— Address area	1 through 49 999 (Standard Modbus addressing)
----------------	---

Interrupts/diagnostics/status information

Diagnostic functions	Yes
----------------------	-----

Diagnostics indication LED

• for status of the outputs	Yes
-----------------------------	-----

Degree and class of protection

Degree of protection acc. to EN 60529

• IP20	Yes
--------	-----

Standards, approvals, certificates

CE mark	Yes
---------	-----

cULus	Yes
-------	-----

FM approval	Yes
-------------	-----

RCM (formerly C-TICK)	Yes
-----------------------	-----

KC approval	Yes
-------------	-----

Ambient conditions

Free fall	
• Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
• min.	-20 °C
• max.	60 °C
• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C
• permissible temperature change	5°C to 55°C, 3°C / minute
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	
• Operation, min.	795 hPa
• Operation, max.	1 080 hPa
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
Relative humidity	
• Operation at 25 °C without condensation, max.	95 %
Dimensions	
Width	30 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	155 g
last modified:	05/15/2018