



Figure similar

MLFB-Ordering data

1PH8131-1FF02-0BA1

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

### Engineering data

	$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \phi$	$I_\mu$ [A]
<b>ALM 400V</b>	<b>13.0</b>	<b>71.0</b>	<b>24.0</b>	<b>416</b>	<b>59.8</b>	<b>1750</b>	<b>140</b>	<b>48.0</b>	<b>8000.0</b>	<b>96.0</b>	<b>30</b>	<b>0.914</b>	<b>0.84</b>	<b>10.3</b>
BLM/SLM 400V	11.0	70.0	24.0	360	51.4	1500	140	48.0	8000.0	96.0	30	0.899	0.84	10.4
ALM/BLM/SLM 480V	15.0	72.0	24.0	460	68.2	2000	140	48.0	8000.0	96.0	30	0.931	0.86	9.2

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	RIA
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft extension	Plain shaft
Encoder system	Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm

### Connection

Type of electrical connection	Terminal box
Terminal box position	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

### Physical constants

Thermal time constant	30 min
Moment of inertia	0.05900 kgm <sup>2</sup>
Weight (approx.)	89 kg

MLFB-Ordering data

1PH8131-1FF02-0BA1



Figure similar

## Cooling data and sound pressure level

Airflow, min.	0.09 m <sup>3</sup> /s
---------------	------------------------

Sound pressure level LpA(1m) motor +  
external fan operation 50 HZ rated 70 dB \*  
load, tolerance + 3dB

Air discharge	axial
---------------	-------

Pressure drop	140 Pa
---------------	--------

\* at a rated frequency of 4 kHz and a speed range of up to 5000 rpm