



Figure similar

MLFB-Ordering data

1PH8135-1JF10-0BA2

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \phi$	I_{μ} [A]
ALM 400V	21.5	117.0	43.0	383	59.6	1750	300	112.0	8000.0	157.0	53	0.909	0.84	18.3
BLM/SLM 400V	18.5	118.0	43.0	330	51.3	1500	300	112.0	8000.0	157.0	53	0.898	0.85	18.1
ALM/BLM/SLM 480V	24.0	115.0	43.0	434	67.9	2000	300	112.0	8000.0	157.0	53	0.929	0.84	18.1

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft extension	Plain shaft
Encoder system	Incremental encoder HTL 2048 S/R, max. encoder speed = 4600 rpm

Connection

Type of electrical connection	Terminal box
Terminal box position	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

Physical constants

Thermal time constant	30 min
Moment of inertia	0.09400 kgm ²
Weight (approx.)	125 kg

MLFB-Ordering data

1PH8135-1JF10-0BA2



Figure similar

Cooling data and sound pressure level

Airflow, min.	0.09 m ³ /s
---------------	------------------------

Sound pressure level LpA(1m) motor +
external fan operation 50 HZ rated 70 dB *
load, tolerance + 3dB

Air discharge	axial
---------------	-------

Pressure drop	140 Pa
---------------	--------

* at a rated frequency of 4 kHz and a speed range of up to 5000 rpm