



Figure similar

MLFB-Ordering data

1PH8137-1DF02-1LA1

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \phi$	I_μ [A]
ALM 400V	25.0	136.0	56.0	353	59.6	1750	380	151.0	10000.0	172.0	68	0.907	0.84	23.1
BLM/SLM 400V	22.0	140.0	56.0	308	51.3	1500	380	151.0	10000.0	172.0	68	0.904	0.84	24.2
ALM/BLM/SLM 480V	28.0	134.0	55.0	401	67.9	2000	380	151.0	10000.0	172.0	68	0.931	0.84	23.1

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SPECIAL/B
Shaft and flange accuracy	SPECIAL
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Performance
Shaft extension	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Connection

Type of electrical connection	Terminal box
Terminal box position	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

Physical constants

Thermal time constant	30 min
Moment of inertia	0.10900 kgm ²
Weight (approx.)	141 kg

MLFB-Ordering data

1PH8137-1DF02-1LA1



Figure similar

Cooling data and sound pressure level

Airflow, min.	0.09 m ³ /s
---------------	------------------------

Sound pressure level LpA(1m) motor +
external fan operation 50 HZ rated 70 dB *
load, tolerance + 3dB

Air discharge	axial
---------------	-------

Pressure drop	140 Pa
---------------	--------

* at a rated frequency of 4 kHz and a speed range of up to 5000 rpm