



Figure similar

MLFB-Ordering data

1PH8165-1DD03-1HB1

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

### Engineering data

	$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \phi$	$I_{\mu}$ [A]
<b>ALM 400V</b>	<b>31.0</b>	<b>257.0</b>	<b>69.0</b>	<b>333</b>	<b>39.2</b>	<b>1150</b>	<b>740</b>	<b>192.0</b>	<b>6500.0</b>	<b>302.0</b>	<b>77</b>	<b>0.921</b>	<b>0.89</b>	<b>20.9</b>
BLM/SLM 400V	28.0	267.0	71.0	292	34.2	1000	740	192.0	6500.0	302.0	77	0.914	0.89	22.2
ALM/BLM/SLM 480V	34.0	241.0	66.0	387	45.8	1350	740	192.0	6500.0	302.0	77	0.928	0.86	22.5

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

### Connection

Type of electrical connection	Terminal box
Terminal box position	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	gk863

### Physical constants

Thermal time constant	35 min
Moment of inertia	0.23200 kgm <sup>2</sup>
Weight (approx.)	230 kg

MLFB-Ordering data

1PH8165-1DD03-1HB1



Figure similar

## Cooling data and sound pressure level

Airflow, min.	0.16 m <sup>3</sup> /s
---------------	------------------------

Sound pressure level LpA(1m) motor +  
external fan operation 50 HZ rated 73 dB \*  
load, tolerance + 3dB

Air discharge	axial
---------------	-------

Pressure drop	200 Pa
---------------	--------

\* at a rated frequency of 4 kHz and a speed range of up to 5000 rpm