



Figure similar

MLFB-Ordering data

1PH8184-1FF00-1BA1

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \phi$	I_{μ} [A]
ALM 400V	60.0	327.0	120.0	390	58.9	1750	925	300.0	5000.0	327.0	120	0.944	0.79	64.0
BLM/SLM 400V	51.0	325.0	116.0	335	50.6	1500	925	300.0	5000.0	325.0	116	0.940	0.80	63.0
ALM/BLM/SLM 480V	68.0	325.0	118.0	450	67.2	2000	925	300.0	5000.0	325.0	118	0.947	0.78	65.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with full key balancing
Encoder system	Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm

Connection

Type of electrical connection	Terminal box
Terminal box position	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7322-P05

Physical constants

Thermal time constant	22 min
Moment of inertia	0.48900 kgm ²
Weight (approx.)	350 kg

MLFB-Ordering data

1PH8184-1FF00-1BA1



Figure similar

Cooling data and sound pressure level

Airflow, min.	0.17 m ³ /s
---------------	------------------------

Sound pressure level LpA(1m) motor +
external fan operation 50 HZ rated 73 dB *
load, tolerance + 3dB

Air discharge	axial
---------------	-------

Pressure drop	550 Pa
---------------	--------

* at a rated frequency of 2 kHz and a speed range of up to 5000 rpm