

SIMATIC ET 200SP, Analog input module, AI 8xRTD/TC 2-wire High Feature Pack quantity: 10 units, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%



General information	
Product type designation	AI 8xRTD/TC 2-wire HF
Firmware version	V2.0
<ul style="list-style-type: none"> FW update possible 	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V13
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 / -
<ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision 	GSD Revision 5
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	GSDML V2.3
Operating mode	
<ul style="list-style-type: none"> Oversampling 	No
<ul style="list-style-type: none"> MSI 	No

CiR – Configuration in RUN

Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

Input current

Current consumption, max.	35 mA
---------------------------	-------

Power loss

Power loss, typ.	0.75 W
------------------	--------

Address area

Address space per module	
• Address space per module, max.	16 byte; + 1 byte for QI information

Analog inputs

Number of analog inputs	8
• For voltage measurement	8
• For resistance/resistance thermometer measurement	8
• For thermocouple measurement	8
permissible input voltage for voltage input (destruction limit), max.	30 V
Constant measurement current for resistance-type transmitter, typ.	2 mA
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels)
Technical unit for temperature measurement adjustable	Yes; °C/°F/K

Input ranges (rated values), voltages

• -1 V to +1 V	Yes; 16 bit incl. sign
• Input resistance (-1 V to +1 V)	1 M Ω
• -250 mV to +250 mV	Yes; 16 bit incl. sign
• Input resistance (-250 mV to +250 mV)	1 M Ω
• -50 mV to +50 mV	Yes; 16 bit incl. sign
• Input resistance (-50 mV to +50 mV)	1 M Ω
• -80 mV to +80 mV	Yes; 16 bit incl. sign
• Input resistance (-80 mV to +80 mV)	1 M Ω

Input ranges (rated values), thermocouples

• Type B	Yes; 16 bit incl. sign
• Input resistance (Type B)	1 M Ω

- Type C
- Input resistance (Type C)
- Type E
- Input resistance (Type E)
- Type J
- Input resistance (type J)
- Type K
- Input resistance (Type K)
- Type L
- Input resistance (Type L)
- Type N
- Input resistance (Type N)
- Type R
- Input resistance (Type R)
- Type S
- Input resistance (Type S)
- Type T
- Input resistance (Type T)
- Type U
- Input resistance (Type U)
- Type TXK/TXK(L) to GOST
- Input resistance (Type TXK/TXK(L) to GOST)

Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ

Input ranges (rated values), resistance thermometer

- Ni 100
- Input resistance (Ni 100)
- Ni 1000
- Input resistance (Ni 1000)
- LG-Ni 1000
- Input resistance (LG-Ni 1000)
- Ni 120
- Input resistance (Ni 120)
- Ni 200
- Input resistance (Ni 200)
- Ni 500
- Input resistance (Ni 500)
- Pt 100
- Input resistance (Pt 100)
- Pt 1000
- Input resistance (Pt 1000)
- Pt 200
- Input resistance (Pt 200)

Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ
Yes; 16 bit incl. sign
1 MΩ

• Pt 500	Yes; 16 bit incl. sign
• Input resistance (Pt 500)	1 M Ω
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes; 15 bit
• Input resistance (0 to 150 ohms)	1 M Ω
• 0 to 300 ohms	Yes; 15 bit
• Input resistance (0 to 300 ohms)	1 M Ω
• 0 to 600 ohms	Yes; 15 bit
• Input resistance (0 to 600 ohms)	1 M Ω
• 0 to 3000 ohms	Yes; 15 bit
• Input resistance (0 to 3000 ohms)	1 M Ω
• 0 to 6000 ohms	Yes; 15 bit
• Input resistance (0 to 6000 ohms)	1 M Ω
• PTC	Yes; 15 bit
• Input resistance (PTC)	1 M Ω
Thermocouple (TC)	
Temperature compensation	
— parameterizable	Yes
— Reference channel of the module	Yes
— internal comparison point	Yes; with BaseUnit type A1
— Reference channel of the group	Yes
— Number of reference channel groups	4; Group 0 to 3
— fixed reference temperature	Yes
Cable length	
• shielded, max.	200 m; 50 m with thermocouples
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Basic conversion time, including integration time (ms)	
— additional processing time for wire-break check	2 ms; In the ranges resistance thermometers, resistors and thermocouples
• Interference voltage suppression for interference frequency f1 in Hz	16.6 / 50 / 60 Hz
• Conversion time (per channel)	180 / 60 / 50 ms
Smoothing of measured values	
• Number of smoothing levels	4; None; 4/8/16 times
• parameterizable	Yes

Encoder

Connection of signal encoders

• for voltage measurement	Yes
• for resistance measurement with two-wire connection	Yes
• for resistance measurement with three-wire connection	No
• for resistance measurement with four-wire connection	No

Errors/accuracies

Linearity error (relative to input range), (+/-)	0.01 %; ±0.1 % for resistance thermometers and resistance
Temperature error (relative to input range), (+/-)	0.0009 %/K; ±0.005 % / K at thermocouple
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.1 %
• Resistance, relative to input range, (+/-)	0.1 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.05 %
• Resistance, relative to input range, (+/-)	0.05 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, f_1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	70 dB
• Common mode voltage, max.	10 V
• Common mode interference, min.	90 dB

Isochronous mode

Isochronous operation (application synchronized up to terminal)	No
---	----

Interrupts/diagnostics/status information

Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Limit value alarm	Yes; two upper and two lower limit values in each case
Diagnostic messages	
• Monitoring the supply voltage	Yes
• Wire-break	Yes; channel by channel
• Group error	Yes
• Overflow/underflow	Yes; channel by channel
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; Green LED

- for channel diagnostics
- for module diagnostics

Yes; Red LED
 Yes; green/red DIAG LED

Potential separation

Potential separation channels

- between the channels
- between the channels and backplane bus
- between the channels and the power supply of the electronics

No
 Yes
 Yes

Permissible potential difference

between the inputs (UCM)

10 V DC

Isolation

Isolation tested with

707 V DC (type test)

Dimensions

Width

15 mm

Height

73 mm

Depth

58 mm

Weights

Weight, approx.

32 g

last modified:

10/30/2018