

Power Contactors for Switching Motors

Accessories and Spare Parts for SIRIUS 3RT Contactors and SIRIUS 3RH2 Contactor Relays

Accessories

Auxiliary switch blocks, delayed

Selection and ordering data

For contactors	Time setting range t	SD	Screw terminals	PU (UNIT, SET, M)	PS*	PG
Type	s	d	Article No.	Price per PU		
Pneumatic time-delay auxiliary switch blocks for mounting on 3RT2 contactors						
Size S0						
Auxiliary contacts 1 NO and 1 NC¹⁾						
ON-delay						
 3RT2926-2P...	3RT202	0.1 ... 30	10	3RT2926-2PA01	1	1 unit 41B
		0.1 ... 30 ²⁾	X	3RT2926-2PA01-OMT0	1	1 unit 41B
		1 ... 60	10	3RT2926-2PA11	1	1 unit 41B
		1 ... 60 ²⁾	X	3RT2926-2PA11-OMT0	1	1 unit 41B
OFF-delay						
	3RT202	0.1 ... 30	10	3RT2926-2PR01	1	1 unit 41B
		0.1 ... 30 ²⁾	X	3RT2926-2PR01-OMT0	1	1 unit 41B
		1 ... 60	10	3RT2926-2PR11	1	1 unit 41B
		1 ... 60 ²⁾	X	3RT2926-2PR11-OMT0	1	1 unit 41B

¹⁾ In addition to these, no other auxiliary contacts are permitted.

²⁾ Certificate for furnaces according to EN 50156-1 on request.

Technical specifications, [see Manual](#).

PU (UNIT, SET, M) = 1
PS* = 1 unit
PG = 41B



3RA2813-1FW10



3RA2813-2AW10

For contactors	Rated control supply voltage $U_s^{1)}$	Time setting range t	Output/auxiliary contacts	SD	Screw terminals		SD	Spring-type terminals	
Type	V	s		d	Article No.	Price per PU	d	Article No.	Price per PU
Solid-state time-delay auxiliary switch blocks ²⁾ for mounting onto 3RT2 contactors and 3RH2 contactor relays									
Sizes S00 to S3									
The electrical connection between the solid-state time-delay auxiliary switch and the contactor or contactor relay underneath is established automatically when it is snapped on and locked.									
ON-delay (varistor integrated)									
3RT2 ³⁾⁴⁾ , 3RH21 ³⁾ , 3RH24	24 ... 240 AC/DC	0.05 ...100 (1, 10, 100 selectable)	1 CO	2	3RA2813-1AW10	2		3RA2813-2AW10	
			1 NO + 1 NC	2	3RA2813-1FW10	2	3RA2813-2FW10		
OFF-delay with control signal (varistor integrated)									
3RT2 ³⁾⁴⁾ , 3RH21 ³⁾ , 3RH24	24 ... 240 AC/DC	0.05 ...100 (1, 10, 100 selectable)	1 CO	2	3RA2814-1AW10	2		3RA2814-2AW10	
			1 NO + 1 NC	2	3RA2814-1FW10	2	3RA2814-2FW10		
OFF-delay without control signal ⁵⁾ (varistor integrated)									
3RT2 ³⁾⁴⁾ , 3RH21 ³⁾ , 3RH24	24 ... 240 AC/DC	0.05 ...100 (1, 10, 100 selectable)	1 CO	2	3RA2815-1AW10	2		3RA2815-2AW10	
			1 NO + 1 NC	2	3RA2815-1FW10	2	3RA2815-2FW10		

¹⁾ AC voltage values apply for 50 Hz and 60 Hz.

²⁾ The solid-state time-delay auxiliary switch blocks are also available as 3RA28 function modules for mounting on 3RT2 contactors and 3RH2 contactor relays, [see page 3/106](#).

³⁾ Cannot be fitted onto coupling relays and coupling contactor relays.

⁴⁾ From product version E04 onwards, 3RA281. solid-state time-delayed auxiliary switch blocks can be used for 3RT2.4 contactors.

⁵⁾ Setting of output contacts in as-supplied state not defined (bistable relay). Application of the control supply voltage once results in contact change-over to the correct setting.

Technical specifications, [see page 3/83](#).