



Figure similar

MLFB-Ordering data

6SL3210-5FE17-0UA0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

| Rated data          |                           | Ambient conditions           |               |
|---------------------|---------------------------|------------------------------|---------------|
| <b>Input</b>        |                           | <b>Cooling</b>               | Fan           |
| Number of phases    | 3 AC                      | <b>Installation altitude</b> | 1000 m        |
| Line voltage        | 380 ... 480 V +10 % -15 % | <b>Ambient temperature</b>   |               |
| Line frequency      | 45 ... 66 Hz              | <b>Operation</b>             | 0 ... 45 °C   |
| <b>Output</b>       |                           | <b>Storage</b>               | -40 ... 70 °C |
| Rated power         | 7.00 kW                   | <b>Relative humidity</b>     |               |
| Rated current (IN)  | 13.20 A                   | <b>Max. operation</b>        | 90 %          |
| Max. output current | 39.60 A                   |                              |               |

| Inputs / outputs               |    | Standards                        |                                  |
|--------------------------------|----|----------------------------------|----------------------------------|
| <b>Standard digital inputs</b> |    | <b>Compliance with standards</b> | CE, KC, cULus, EAC, C-Tick (RCM) |
| Number                         | 10 |                                  |                                  |
| <b>Digital outputs</b>         |    |                                  |                                  |
| Number                         | 6  |                                  |                                  |
| <b>Analog inputs</b>           |    |                                  |                                  |
| Number                         | 2  |                                  |                                  |
| <b>Analog outputs</b>          |    |                                  |                                  |
| Number                         | 2  |                                  |                                  |

| Mechanical data             |                     |
|-----------------------------|---------------------|
| <b>Degree of protection</b> | IP20 / UL open type |
| <b>Size</b>                 | FSC                 |
| <b>Net weight</b>           | 5.65 kg             |
| <b>Width</b>                | 140.0 mm            |
| <b>Height</b>               | 260.0 mm            |
| <b>Depth</b>                | 240.0 mm            |