

Technical data sheet - LÜTZE SILFLEX® Tray-ER PVC with UL/TC-ER/WTTC/MTW/CE Approvals



Flexible Tray Cable · Unshielded

Identification	Type	SI TRAY-ER PVC 4xAWG8
	Part-No.	A3220804

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • Multi-conductor cable for tray applications, with exposed run (open wiring) approval • Compliant with NFPA 79 for machine tool wiring • TC-ER for use with cable trays without conduit, which can reduce material and labor costs • Machine tools, machine and plant construction, HVAC technology, assembly and production lines, and other industrial applications • WTTC – wind turbine tray cable rating for use in wind power generation • Dry, damp and wet conditions
Characteristics	<ul style="list-style-type: none"> • Flexible design with Nylon for crush impact resistance per UL 1277 and easy installation • Specially formulated jacket for oil resistance • Non-wicking fillers • Sunlight resistant • Direct burial • UL Type TC-Exposed Run • Talc free • Silicone free

Construction

Description	SILFLEX® TRAY-ER PVC
-------------	----------------------

25.01.2020 – Subject to technical modification

Part-No. A3220804

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet - LÜTZE SILFLEX® Tray-ER PVC with UL/TC-ER/WTTC/MTW/CE Approvals

Number of conductors/cross-section	4xAWG8
Cross-section AWG	AWG 8
Cross-section, metric	10 mm ²
Jacket material	PVC
Jacket color	black RAL 9005
Outer Ø	18.9 mm
Outer Ø	0.744 inch
Weight	58.8 kg/100 m
Weight	366 Lbs/Mft
Cu-Index	31.8 kg/100 m
Cu-Index	124 Lbs/Mft

Element 1

Element construction	AWG8/4C
Conductor	AWG conductor CU-wire bare
Conductor category	fine wire
Conductor marking	black with white number print green/yellow
Conductor insulation	PVC/Nylon

overall construction

Jacket characteristics	Oil resistant UV resistant (normal lighting conditions) Silicone-free
------------------------	---

Technical data

Rated voltage U _N	600 V TC-ER 1000 V WTTC
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	4xD

Element 1

Element construction	AWG8/4C
----------------------	---------

Certifications/Standards

25.01.2020 – Subject to technical modification

Part-No. A3220804

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet - LÜTZE SILFLEX® Tray-ER PVC with UL/TC-ER/WTTC/MTW/CE Approvals

Certifications	TC-ER cURus cULus UL Type MTW or DP-1 WTTC Meets NEC 336,392 Class I & II, Div. 2 Class 1 Div. 2 per NEC 501, 502, 505 cUL TC CIC FT4 UL 1277
UL style	AWM 20886
Conformity	CE REACH RoHS
Oil resistant according to	Oil Res II

General

Note CE These products are in conformity with the EU Low Voltage Directive 2014/35/EU

Symbols



25.01.2020 – Subject to technical modification

Part-No. A3220804

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY