



mounting position	Any, preferably vertical		
<b>Environmental conditions</b>			
ambient temperature / during operation			
• minimum	-20 °C		
• maximum	50 °C		
environmental category	-20 to +50 at 95% relative humidity		
<b>Certificates</b>			
reference code			
• acc. to DIN EN 61346-2	F		
• acc. to IEC 81346-2	F		
<b>General Product Approval</b>	<b>Declaration of Conformity</b>	<b>Test Certificates</b>	<b>other</b>



[Special Test Certificate](#)

[Miscellaneous](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE1435-0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3NE1435-0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NE1435-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE1435-0)

**Tender specifications**

<http://www.siemens.com/specifications>

