

DIAZED FUSE LINK 500V F.CABLE AND LINE PROTECTION
OP.CL.GL,SZ.DII,THREAD E27,4A



Figure similar

Model	
product brandname	SETRON
Product designation	DIAZED fuse
Design of the product	For cable and line protection
Design of the fuse link	DIAZED fuse link
General technical data	
Tripping characteristic class	Other
Size of fuse system / acc. to DIN EN 60269-1	DII
Operating class of the fuse link	gG
circuit-breaker / Design	5SB2
Supply voltage	
• at AC / rated value	500 V
• at DC	500 V
Protection class	
Protection class IP	IP20, with connected conductors
Switching capacity	

Switching capacity current	
• at DC / acc. to IEC 60947-2 / rated value	8 kA
• acc. to IEC 60947-2 / rated value	50 kA
Dissipation	
Power loss [W]	2 W
Power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	2 W
• maximum	2 W
Electricity	
rated current I _n / IEC, DIN/VDE / at 40 °C	3.8 A
Current / at AC / rated value	4 A
Appearance	
Color coding of the fuse link	brown
Product details	
Product description	Using screw adapter or adapter sleeves
Mechanical Design	
Mounting position	Any, preferably vertical
Net weight	27 g
Environmental conditions	
Ambient temperature	
• minimum	-5 °C
• maximum	40 °C
• during storage	Air humidity 90% at 20 °C
Environmental category	Up to 45°C at 95 % rel. humidity
Equipment marking	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval			Declaration of Conformity	Test Certificates	
				Type Test Certificates/Test Report	Special Test Certificate
KEMA	ÖVE	VDE	EG-Konf.		

Shipping Approval	other
-------------------	-------



GL

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SB221>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SB221>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SB221

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

