

product type designation



Figure similar

Reader RF340R (EX)

SIMATIC RF300; Reader RF340R (GEN2); RS422 interface (3964R); IP67, -25 to +70 °C, 75x 75x 41 mm with integrated antenna special variant ATEX (Zone 3G/3D) and IECEx (Gc/Dc) for Zone 2/22 .

suitability for operation

RF300, ISO 15693 and MOBY E transponder, for connecting to communication modules, EX: II 3 G Ex ec IIB T4 Gc, II 3 D Ex tc IIIC T80 °C Dc

radio frequencies

operating frequency / rated value	13.56 MHz
range / maximum	140 mm; Range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	RF300 specific, ISO 15693, ISO 18000-3, ISO 14443
transfer rate / with radio transmission / maximum	106 kbit/s
product feature / multitag-capable	No

electrical data

transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
transmission time / for user data	
• for write access / per byte / typical	0.13 ms
• for read access / per byte / typical	0.13 ms

interfaces

standard for interfaces / for communication	RS422
type of electrical connection	M12, 8-pin

mechanical data

material	PA 12
color	Ti gray
tightening torque / of the screw for securing the equipment / maximum	1.5 N·m
mounting distance / relating to metal surfaces / recommended / minimum	0 mm

supply voltage, current consumption, power loss

supply voltage / at DC	
• rated value	24 V
•	20.4 ... 28.8 V
consumed current / at DC	
• at 24 V / typical	0.06 A

ambient conditions

ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
protection class IP	IP64
shock resistance	EN 60721-3-7 Class 7 M2
shock acceleration	500 m/s²
vibrational acceleration	200 m/s²

design, dimensions and weights					
width	75 mm				
height	41 mm				
depth	75 mm				
net weight	0.25 kg				
fastening method	2 x M5 screws				
wire length					
• for RS 422 interface / maximum	1000 m				
product features, product functions, product components / general					
display version	5-color LED				
product feature / silicon-free	Yes				
standards, specifications, approvals					
certificate of suitability	Radio acc. to R&TTE guidelines EN 300 330, EN 301489, CE, FCC, cULus, ATEX: EN 60079-0:2012+A11:2013, EN 60079-7:2015, EN60079-31:2014, IEC Ex: IEC 60079-0:2011, IEC 60079-31:2013, EN 60079-7:2015, UL HAZ.LOC: UL 60079-0, CSA C22.2 NO.60079-0, UL 60079-7, CSA C22.2 NO. 60079-7, UL 60079-31, CSA C22.2 NO. 60079-31				
certificate of suitability					
• IECEx	Yes				
• for IECEx / as marking	EX: II 3 G Ex ec IIB T4 Gc, II 3 D Ex tc IIIC T80 °C Dc				
MTBF	260 a				
standards, specifications, approvals / Environmental Product Declaration					
Environmental Product Declaration	Yes				
Global Warming Potential [CO2 eq]					
• total	124.25 kg				
• during manufacturing	11.24 kg				
• during operation	112.71 kg				
• after end of life	0.3 kg				
further information / internet links					
internet link					
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358				
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud				
• to web page: RFID country approval	https://www.siemens.com/rfid-approvals				
• to website: Image database	https://www.automation.siemens.com/bilddb				
• to website: CAx-Download-Manager	https://www.siemens.com/cax				
• to website: Industry Online Support	https://support.industry.siemens.com				
security information					
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)				
Approvals / Certificates					
General Product Approval	EMV	For use in hazardous locations			
	 EG-Konf.	 RCM	 KC	 IECEX	 ATEX
For use in hazardous locations		Radio Equipment Type Approval Certi-	Environment		

[CCC-Ex](#)



[Miscellaneous](#)



last modified:

5/18/2024 