

Device adapter MCCB, 3-pole, 590 A Busbar center-to-center spacing 60 mm for 3VA53/54/23/24/63/64 300 x 140 mm Contacting elements for the adapter are provided



Model	
Product brand name	SENTRON
Product designation	Device adapter
Design of the product	Accessories
Insulation voltage / rated value	800 V
Surge voltage resistance / rated value	6 kV
Dissipation	
Power loss [W]	87 W
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	42 W
Current / at AC / rated value	590 A
Operating voltage / at AC / rated value	690 V
Height	300 mm
Width	140 mm
Busbar center-to-center spacing	60 mm
Net weight	2 500 g
Certificates	

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
 UL		 EG-Konf.	Special Test Certificate Miscellaneous
			 PRS

Shipping Approval	other
 RINA	Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1213-4AH04>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1213-4AH04>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1213-4AH04

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



