

## Data sheet for SIMOTICS S-1FT7



Figure similar

MLFB-Ordering data

1FT7105-5AF71-1FH1-Z  
J02

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data																					
Rated speed	3000 rpm	Motor type	Permanent-magnet synchronous motor																				
Number of poles	10	Design of the motor type	Compact																				
Rated torque (100 K)	28.0 Nm	Shaft height	100 mm																				
Rated current	15.0 A	Cooling	Natural cooling																				
Static torque (60 K)	41.00 Nm	Radial runout tolerance	N																				
Static torque (100 K)	50.0 Nm	Vibration severity grade	Grade A																				
Stall current (60 K)	21.0 A	Connector size	1.5																				
Stall current (100 K)	26.0 A	Degree of protection	IP65																				
Rotor moment of inertia	0.0239900 kgm <sup>2</sup>	Design acc. to Code I	IM B5 (compatible with 1FT6)																				
<table border="1"> <thead> <tr> <th colspan="2">Physical constants</th> </tr> </thead> <tbody> <tr> <td>Torque constant</td> <td>1.92 Nm/A</td> </tr> <tr> <td>Voltage constant at 20° C</td> <td>123.5 V/1000*min<sup>-1</sup></td> </tr> <tr> <td>Winding resistance at 20° C</td> <td>0.08 Ω</td> </tr> <tr> <td>Rotating field inductance</td> <td>2.3 mH</td> </tr> <tr> <td>Electrical time constant</td> <td>27.00 ms</td> </tr> <tr> <td>Mechanical time constant</td> <td>1.20 ms</td> </tr> <tr> <td>Thermal time constant</td> <td>80 min</td> </tr> <tr> <td>Shaft torsional stiffness</td> <td>107000 Nm/rad</td> </tr> <tr> <td>Net weight of the motor</td> <td>84.4 kg</td> </tr> </tbody> </table>		Physical constants		Torque constant	1.92 Nm/A	Voltage constant at 20° C	123.5 V/1000*min <sup>-1</sup>	Winding resistance at 20° C	0.08 Ω	Rotating field inductance	2.3 mH	Electrical time constant	27.00 ms	Mechanical time constant	1.20 ms	Thermal time constant	80 min	Shaft torsional stiffness	107000 Nm/rad	Net weight of the motor	84.4 kg	Temperature monitoring	Pt1000 temperature sensor
		Physical constants																					
Torque constant	1.92 Nm/A																						
Voltage constant at 20° C	123.5 V/1000*min <sup>-1</sup>																						
Winding resistance at 20° C	0.08 Ω																						
Rotating field inductance	2.3 mH																						
Electrical time constant	27.00 ms																						
Mechanical time constant	1.20 ms																						
Thermal time constant	80 min																						
Shaft torsional stiffness	107000 Nm/rad																						
Net weight of the motor	84.4 kg																						
<table border="1"> <thead> <tr> <th colspan="2">Recommended Motor Module</th> </tr> </thead> <tbody> <tr> <td>Rated inverter current</td> <td>30 A</td> </tr> <tr> <td>Maximum inverter current</td> <td>90 A</td> </tr> <tr> <td>Maximum torque</td> <td>157.00 Nm</td> </tr> </tbody> </table>		Recommended Motor Module		Rated inverter current	30 A	Maximum inverter current	90 A	Maximum torque	157.00 Nm	Electrical connectors	Connector turnable												
		Recommended Motor Module																					
Rated inverter current	30 A																						
Maximum inverter current	90 A																						
Maximum torque	157.00 Nm																						
		Color of the housing																					
		Holding brake version	Permanent-magnet brake																				
		Shaft end type	Plain shaft																				
		Sensor design	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)																				



Figure similar

MLFB-Ordering data

1FT7105-5AF71-1FH1-Z  
J02

### Gearbox data

Gearbox type	Planetary gearbox	Moment of inertia of gearbox	0.0033900 kgm <sup>2</sup>
Designation	SP 180S-MF1	Radial output shaft loading, max.	14700 N
Gearbox ratio	4	Axial output shaft load, max.	14150 N
Motor speed S3-60 %	3500 rpm	Efficiency of gearbox	0.97
Motor speed S1	1500 rpm	Torsional backlash	3 '
Output torque S1	750 Nm	Gearbox weight	34.00 kg
Rated output torque at duty type S3-60 %	1100 Nm		

### Limiting data

Max. permissible speed (mech.)	6000 rpm
Max. permissible speed (inverter)	4630 rpm
Maximum torque	200.0 Nm
Maximum current	116.0 A

### Special design

J02 Mounting of SP+ planetary gearbox