


LED A19-A21

Dimensional drawing



Operating and Electrical	
Voltage (Nom)	120 V
Starting Time (Nom)	0.5 s
General Information	
Cap-Base	E26
Light Technical	
Llmf At End Of Nominal Lifetime (Nom)	70 %

Product	D	C
8.8A19/PER/930/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
5A19/PER/950/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
5A19/PER/930/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
8.8A19/PER/940/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
8.8A19/PER/927/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
8.8A19/PER/950/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
5A19/PER/927/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
5A19/PER/940/P/E26/DIM 6/1FB T20	62.5 mm	111.5 mm
8.8A19/LED/927/P/E26/ND 6/1FB T20	61 mm	112 mm
8.8A19/LED/950/P/E26/ND 6/1FB T20	61 mm	112 mm

Controls and Dimming

Order Code	Full Product Name	Dimmable
466565	BC8A19/AMB/827/ND D2D 120V 4/1	No
465187	BC10A19/AMB/927/DIM 120V 4/1	Yes
531798	9A19/LED/927/P/E26/ND 4/4FB T20	No
531806	9A19/LED/950/P/E26/ND 4/4FB T20	No
531772	18A21/LED/927/P/E26/ND 4/2FB T20	No
531764	18A21/LED/950/P/E26/ND 4/2FB T20	No
479469	12.2A21/PER/927-22/P/E26/WG 6/1FB T20	Yes
479485	16A21/PER/927-22/P/E26/WG 6/1FB T20	Yes
550475	12.2A21/PER/927/P/E26/DIM 6/1FB T20	Yes
550483	12.2A21/PER/930/P/E26/DIM 6/1FB T20	Yes
547091	12.2A21/PER/940/P/E26/DIM 6/1FB T20	Yes
550491	12.2A21/PER/950/P/E26/DIM 6/1FB T20	Yes
550509	16A21/PER/927/P/E26/DIM 6/1FB T20	Yes
550517	16A21/PER/930/P/E26/DIM 6/1FB T20	Yes
547125	16A21/PER/940/P/E26/DIM 6/1FB T20	Yes
550525	16A21/PER/950/P/E26/DIM 6/1FB T20	Yes
554469	16.6A21/LED/927/P/E26/ND 6/1FB T20	No
538322	9.5A19/AMB/827-822/DIM 120V 2PK 4/2	Yes
479428	5A19/PER/927-22/P/E26/WG 6/1FB T20	Yes
479444	8.8A19/PER/927-22/P/E26/WG 6/1FB T20	Yes
477612	6A19/PER/850/CL/G/DIM 4/2BC	Yes
548214	6.5A19/LED/827/FR/P/ND 4/2FB	No
461145	6.5A19/LED/827/FR/P/ND 4/4FB	No

Order Code	Full Product Name	Dimmable
548222	10A19/LED/827/FR/P/ND 4/2FB	No
461129	10A19/LED/827/FR/P/ND 4/4FB	No
469205	10A19/LED/827/FR/P/ND 4/6FB	No
462184	5.5A19/LED/850/FR/P/ND 4/2FB	No
461160	5.5A19/LED/850/FR/P/ND 4/4FB	No
548230	9A19/LED/850/FR/P/ND 4/2FB	No
461137	9A19/LED/850/FR/P/ND 4/4FB	No
543033	9A19/LED/850/FR/P/ND 4/6FB	No
462969	11A19/LED/827/FR/P/ND 4/2FB	No
542944	11A19/LED/827/FR/P/ND 4/4FB	No
461961	14A19/LED/827/FR/P/ND 4/2FB	No
542950	14A19/LED/827/FR/P/ND 4/4FB	No
463000	10A19/LED/850/FR/P/ND 4/2FB	No
542968	10A19/LED/850/FR/P/ND 4/4FB	No
548248	12.5A19/LED/850/FR/P/ND 4/2FB	No
542976	12.5A19/LED/850/FR/P/ND 4/4FB	No
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	Yes
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	Yes
543116		Yes
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	Yes
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	Yes
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	Yes
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	Yes

LED A19-A21

Order Code	Full Product Name	Dimmable
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	Yes
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	Yes
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	Yes
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	Yes

Order Code	Full Product Name	Dimmable
554428	8.8A19/LED/927/P/E26/ND 6/1FB T20	No
554444	8.8A19/LED/950/P/E26/ND 6/1FB T20	No
549220	5A19/PER/950/CL/G/E26/DIM 1FB T20	Yes
549238		Yes

Operating and Electrical

Order Code	Full Product Name	Input Frequency	Wattage Equivalent	Power (Rated) (Nom)
466565	BC8A19/AMB/827/ND D2D 120V 4/1	60 Hz	60 W	8 W
465187	BC10A19/AMB/927/DIM 120V 4/1	60 Hz	60 W	10 W
531798	9A19/LED/927/P/E26/ND 4/4FB T20	60 Hz	60 W	9 W
531806	9A19/LED/950/P/E26/ND 4/4FB T20	60 Hz	60 W	9 W
531772	18A21/LED/927/P/E26/ND 4/2FB T20	60 Hz	100 W	18 W
531764	18A21/LED/950/P/E26/ND 4/2FB T20	60 Hz	100 W	18 W
479469	12.2A21/PER/927-22/P/E26/WG 6/1FB T20	60 Hz	75 W	12.2 W
479485	16A21/PER/927-22/P/E26/WG 6/1FB T20	60 Hz	100 W	16 W
550475	12.2A21/PER/927/P/E26/DI M 6/1FB T20	60 Hz	75 W	12.2 W
550483	12.2A21/PER/930/P/E26/D IM 6/1FB T20	60 Hz	75 W	12.2 W
547091	12.2A21/PER/940/P/E26/D IM 6/1FB T20	60 Hz	75 W	12.2 W
550491	12.2A21/PER/950/P/E26/D IM 6/1FB T20	60 Hz	75 W	12.2 W
550509	16A21/PER/927/P/E26/DI M 6/1FB T20	60 Hz	100 W	16 W
550517	16A21/PER/930/P/E26/DI M 6/1FB T20	60 Hz	100 W	16 W
547125	16A21/PER/940/P/E26/DI M 6/1FB T20	60 Hz	100 W	16 W
550525	16A21/PER/950/P/E26/DI M 6/1FB T20	60 Hz	100 W	16 W
554469	16.6A21/LED/927/P/E26/N D 6/1FB T20	60 Hz	100 W	16.6 W
538322	9.5A19/AMB/827-822/DIM 120V 2PK 4/2	60 Hz	60 W	9.5 W
479428	5A19/PER/927-22/P/E26/WG 6/1FB T20	60 Hz	40 W	5 W

Order Code	Full Product Name	Input Frequency	Wattage Equivalent	Power (Rated) (Nom)
479444	8.8A19/PER/927-22/P/E26/WG 6/1FB T20	60 Hz	60 W	8.8 W
477612	6A19/PER/850/CL/G/DIM 4/2BC	50 to 60 Hz	40 W	6 W
548214	6.5A19/LED/827/FR/P/ND 4/2FB	60 Hz	40 W	6.5 W
461145	6.5A19/LED/827/FR/P/ND 4/4FB	60 Hz	40 W	6.5 W
548222	10A19/LED/827/FR/P/ND 4/2FB	60 Hz	60 W	10 W
461129	10A19/LED/827/FR/P/ND 4/4FB	60 Hz	60 W	10 W
469205	10A19/LED/827/FR/P/ND 4/6FB	60 Hz	60 W	10 W
462184	5.5A19/LED/850/FR/P/ND 4/2FB	60 Hz	40 W	5.5 W
461160	5.5A19/LED/850/FR/P/ND 4/4FB	60 Hz	40 W	5.5 W
548230	9A19/LED/850/FR/P/ND 4/2FB	60 Hz	60 W	9 W
461137	9A19/LED/850/FR/P/ND 4/4FB	60 Hz	60 W	9 W
543033	9A19/LED/850/FR/P/ND 4/6FB	60 Hz	60 W	9 W
462969	11A19/LED/827/FR/P/ND 4/2FB	60 Hz	75 W	11 W
542944	11A19/LED/827/FR/P/ND 4/4FB	60 Hz	75 W	11 W
461961	14A19/LED/827/FR/P/ND 4/2FB	60 Hz	100 W	14 W
542950	14A19/LED/827/FR/P/ND 4/4FB	60 Hz	100 W	14 W
463000	10A19/LED/850/FR/P/ND 4/2FB	60 Hz	75 W	10 W
542968	10A19/LED/850/FR/P/ND 4/4FB	60 Hz	75 W	10 W
548248	12.5A19/LED/850/FR/P/N D 4/2FB	60 Hz	100 W	12.5 W
542976	12.5A19/LED/850/FR/P/N D 4/4FB	60 Hz	100 W	12.5 W

LED A19-A21

Order Code	Full Product Name	Input Frequency	Wattage Equivalent	Power (Rated) (Nom)
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	50 to 60 Hz	40 W	5 W
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	50 to 60 Hz	60 W	8 W
543116		50 to 60 Hz	25 W	4 W
545897	8.8A19/PER/940/P/E26/DI M 6/1FB T20	60 Hz	60 W	8.8 W
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	60 Hz	40 W	5 W
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	60 Hz	40 W	5 W
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	60 Hz	40 W	5 W

Order Code	Full Product Name	Input Frequency	Wattage Equivalent	Power (Rated) (Nom)
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	60 Hz	40 W	5 W
550434	8.8A19/PER/927/P/E26/DI M 6/1FB T20	60 Hz	60 W	8.8 W
550442	8.8A19/PER/930/P/E26/DI M 6/1FB T20	60 Hz	60 W	8.8 W
550459	8.8A19/PER/950/P/E26/DI M 6/1FB T20	60 Hz	60 W	8.8 W
554428	8.8A19/LED/927/P/E26/N D 6/1FB T20	60 Hz	60 W	8.8 W
554444	8.8A19/LED/950/P/E26/N D 6/1FB T20	60 Hz	60 W	8.8 W
549220	5A19/PER/950/CL/G/E26/DIM 1FB T20	60 Hz	40 W	5 W
549238		60 Hz	60 W	8.8 W

General Information

Order Code	Full Product Name	Nominal Lifetime (Nom)	Switching Cycle
466565	BC8A19/AMB/827/ND D2D 120V 4/1	25000 h	50000X
465187	BC10A19/AMB/927/DIM 120V 4/1	25000 h	50000X
531798	9A19/LED/927/P/E26/ND 4/4FB T20	10950 h	50000X
531806	9A19/LED/950/P/E26/ND 4/4FB T20	10950 h	50000X
531772	18A21/LED/927/P/E26/ND 4/2FB T20	10950 h	50000X
531764	18A21/LED/950/P/E26/ND 4/2FB T20	10950 h	50000X
479469	12.2A21/PER/927-22/P/E26/WG 6/1FB T20	15000 h	50000X
479485	16A21/PER/927-22/P/E26/WG 6/1FB T20	15000 h	50000X
550475	12.2A21/PER/927/P/E26/DIM 6/1FB T20	15000 h	50000X
550483	12.2A21/PER/930/P/E26/DIM 6/1FB T20	15000 h	50000X
547091	12.2A21/PER/940/P/E26/DIM 6/1FB T20	15000 h	50000X
550491	12.2A21/PER/950/P/E26/DIM 6/1FB T20	15000 h	50000X
550509	16A21/PER/927/P/E26/DIM 6/1FB T20	15000 h	50000X
550517	16A21/PER/930/P/E26/DIM 6/1FB T20	15000 h	50000X
547125	16A21/PER/940/P/E26/DIM 6/1FB T20	15000 h	50000X
550525	16A21/PER/950/P/E26/DIM 6/1FB T20	15000 h	50000X
554469	16.6A21/LED/927/P/E26/ND 6/1FB T20	11000 h	50000X
538322	9.5A19/AMB/827-822/DIM 120V 2PK 4/2	15000 h	50000X
479428	5A19/PER/927-22/P/E26/WG 6/1FB T20	15000 h	50000X
479444	8.8A19/PER/927-22/P/E26/WG 6/1FB T20	15000 h	50000X
477612	6A19/PER/850/CL/G/DIM 4/2BC	15000 h	20000X
548214	6.5A19/LED/827/FR/P/ND 4/2FB	11000 h	50000X
461145	6.5A19/LED/827/FR/P/ND 4/4FB	11000 h	50000X
548222	10A19/LED/827/FR/P/ND 4/2FB	11000 h	50000X
461129	10A19/LED/827/FR/P/ND 4/4FB	11000 h	50000X
469205	10A19/LED/827/FR/P/ND 4/6FB	11000 h	50000X
462184	5.5A19/LED/850/FR/P/ND 4/2FB	11000 h	50000X

Order Code	Full Product Name	Nominal Lifetime (Nom)	Switching Cycle
461160	5.5A19/LED/850/FR/P/ND 4/4FB	11000 h	50000X
548230	9A19/LED/850/FR/P/ND 4/2FB	11000 h	50000X
461137	9A19/LED/850/FR/P/ND 4/4FB	11000 h	50000X
543033	9A19/LED/850/FR/P/ND 4/6FB	11000 h	50000X
462969	11A19/LED/827/FR/P/ND 4/2FB	11000 h	50000X
542944	11A19/LED/827/FR/P/ND 4/4FB	11000 h	50000X
461961	14A19/LED/827/FR/P/ND 4/2FB	11000 h	50000X
542950	14A19/LED/827/FR/P/ND 4/4FB	11000 h	50000X
463000	10A19/LED/850/FR/P/ND 4/2FB	11000 h	50000X
542968	10A19/LED/850/FR/P/ND 4/4FB	11000 h	50000X
548248	12.5A19/LED/850/FR/P/ND 4/2FB	11000 h	50000X
542976	12.5A19/LED/850/FR/P/ND 4/4FB	11000 h	50000X
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	15000 h	20000X
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	15000 h	20000X
543116		15000 h	20000X
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	15000 h	50000X
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	15000 h	50000X
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	15000 h	50000X
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	15000 h	50000X
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	15000 h	50000X
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	15000 h	50000X
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	15000 h	50000X
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	15000 h	50000X
554428	8.8A19/LED/927/P/E26/ND 6/1FB T20	11000 h	50000X
554444	8.8A19/LED/950/P/E26/ND 6/1FB T20	11000 h	50000X
549220	5A19/PER/950/CL/G/E26/DIM 1FB T20	15000 h	20000X
549238		15000 h	20000X

LED A19-A21

Light Technical

Order Code	Full Product Name	Beam Angle (Nom)	Color Code	Correlated Color Temperature (Nom)	Color Rendering Index	
					(Nom)	Luminous Flux (Nom)
466565	BC8A19/AMB/827/ND D2D 120V 4/1	220 °	827	2700 K	80	800 lm
465187	BC10A19/AMB/927/DIM 120V 4/1	-	927	2700 K	90	800 lm
531798	9A19/LED/927/P/E26/ND 4/4FB T20	250 °	927	2700 K	90	800 lm
531806	9A19/LED/950/P/E26/ND 4/4FB T20	250 °	950	5000 K	90	800 lm
531772	18A21/LED/927/P/E26/ND 4/2FB T20	250 °	927	2700 K	90	1500 lm
531764	18A21/LED/950/P/E26/ND 4/2FB T20	250 °	950	5000 K	90	1500 lm
479469	12.2A21/PER/927-22/P/E26/WG 6/1FB T20	250 °	922-927	2200-2700 K	90	1100 lm
479485	16A21/PER/927-22/P/E26/WG 6/1FB T20	250 °	922-927	2200-2700 K	90	1600 lm
550475	12.2A21/PER/927/P/E26/DIM 6/1FB T20	250 °	927	2700 K	90	1100 lm
550483	12.2A21/PER/930/P/E26/DIM 6/1FB T20	250 °	930	3000 K	90	1100 lm
547091	12.2A21/PER/940/P/E26/DIM 6/1FB T20	250 °	940	4000 K	90	1100 lm
550491	12.2A21/PER/950/P/E26/DIM 6/1FB T20	250 °	950	5000 K	90	1100 lm
550509	16A21/PER/927/P/E26/DIM 6/1FB T20	250 °	927	2700 K	90	1600 lm
550517	16A21/PER/930/P/E26/DIM 6/1FB T20	250 °	930	3000 K	90	1600 lm
547125	16A21/PER/940/P/E26/DIM 6/1FB T20	250 °	940	4000 K	90	1600 lm
550525	16A21/PER/950/P/E26/DIM 6/1FB T20	250 °	950	5000 K	90	1600 lm
554469	16.6A21/LED/927/P/E26/ND 6/1FB T20	210 °	927	2700 K	90	1500 lm
538322	9.5A19/AMB/827-822/DIM 120V 2PK 4/2	250 °	822-827	2200-2700 K	80	800 lm
479428	5A19/PER/927-22/P/E26/WG 6/1FB T20	250 °	922-927	2200-2700 K	90	450 lm
479444	8.8A19/PER/927-22/P/E26/WG 6/1FB T20	250 °	922-927	2200-2700 K	90	800 lm
477612	6A19/PER/850/CL/G/DIM 4/2BC	-	850	5000 K	80	450 lm
548214	6.5A19/LED/827/FR/P/ND 4/2FB	150 °	827	2700 K	80	450 lm
461145	6.5A19/LED/827/FR/P/ND 4/4FB	150 °	827	2700 K	80	450 lm
548222	10A19/LED/827/FR/P/ND 4/2FB	150 °	827	2700 K	80	800 lm
461129	10A19/LED/827/FR/P/ND 4/4FB	150 °	827	2700 K	80	800 lm
469205	10A19/LED/827/FR/P/ND 4/6FB	150 °	827	2700 K	80	800 lm
462184	5.5A19/LED/850/FR/P/ND 4/2FB	150 °	850	5000 K	80	450 lm
461160	5.5A19/LED/850/FR/P/ND 4/4FB	150 °	850	5000 K	80	450 lm
548230	9A19/LED/850/FR/P/ND 4/2FB	150 °	850	5000 K	80	800 lm
461137	9A19/LED/850/FR/P/ND 4/4FB	150 °	850	5000 K	80	800 lm
543033	9A19/LED/850/FR/P/ND 4/6FB	150 °	850	5000 K	80	800 lm
462969	11A19/LED/827/FR/P/ND 4/2FB	150 °	827	2700 K	80	1000 lm
542944	11A19/LED/827/FR/P/ND 4/4FB	150 °	827	2700 K	80	1000 lm
461961	14A19/LED/827/FR/P/ND 4/2FB	150 °	827	2700 K	80	1500 lm
542950	14A19/LED/827/FR/P/ND 4/4FB	150 °	827	2700 K	80	1500 lm
463000	10A19/LED/850/FR/P/ND 4/2FB	150 °	850	5000 K	80	1000 lm
542968	10A19/LED/850/FR/P/ND 4/4FB	150 °	850	5000 K	80	1000 lm
548248	12.5A19/LED/850/FR/P/ND 4/2FB	150 °	850	5000 K	80	1500 lm
542976	12.5A19/LED/850/FR/P/ND 4/4FB	150 °	850	5000 K	80	1500 lm
549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	300 °	927-922	2700-2200 K	90	450 lm
549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	300 °	927-922	2700-2200 K	90	800 lm
543116		-	841	4000 K	80	150 lm
545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	250 °	940	4000 K	90	800 lm
550400	5A19/PER/927/P/E26/DIM 6/1FB T20	250 °	927	2700 K	90	450 lm
550418	5A19/PER/930/P/E26/DIM 6/1FB T20	250 °	930	3000 K	90	450 lm
547042	5A19/PER/940/P/E26/DIM 6/1FB T20	250 °	940	4000 K	90	450 lm
550426	5A19/PER/950/P/E26/DIM 6/1FB T20	250 °	950	5000 K	90	450 lm
550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	250 °	927	2700 K	90	800 lm
550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	250 °	930	3000 K	90	800 lm
550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	250 °	950	5000 K	90	800 lm

LED A19-A21

Order Code	Full Product Name	Beam Angle (Nom)	Color Code	Correlated Color Temperature (Nom)	Color Rendering Index	
					(Nom)	Luminous Flux (Nom)
554428	8.8A19/LED/927/P/E26/ND 6/1FB T20	210 °	927	2700 K	90	800 lm
554444	8.8A19/LED/950/P/E26/ND 6/1FB T20	210 °	950	5000 K	90	800 lm
549220	5A19/PER/950/CL/G/E26/DIM 1FB T20	-	950	5000 K	90	450 lm
549238		-	950	5000 K	90	800 lm

Mechanical and Housing

Order Code	Full Product Name	Bulb Finish	Bulb Shape	Order Code	Full Product Name	Bulb Finish	Bulb Shape
466565	BC8A19/AMB/827/ND D2D 120V 4/1	Frosted	A19 (A19)	461160	5.5A19/LED/850/FR/P/ND 4/4FB	Frosted	A19 (A19)
465187	BC10A19/AMB/927/DIM 120V 4/1	Frosted	A19 (A19)	548230	9A19/LED/850/FR/P/ND 4/2FB	Frosted	A19 (A19)
531798	9A19/LED/927/P/E26/ND 4/4FB T20	Frosted	A19 (A19)	461137	9A19/LED/850/FR/P/ND 4/4FB	Frosted	A19 (A19)
531806	9A19/LED/950/P/E26/ND 4/4FB T20	Frosted	A19 (A19)	543033	9A19/LED/850/FR/P/ND 4/6FB	Frosted	A19 (A19)
531772	18A21/LED/927/P/E26/ND 4/2FB T20	Frosted	A21 (A21)	462969	11A19/LED/827/FR/P/ND 4/2FB	Frosted	A19 (A19)
531764	18A21/LED/950/P/E26/ND 4/2FB T20	Frosted	A21 (A21)	542944	11A19/LED/827/FR/P/ND 4/4FB	Frosted	A19 (A19)
479469	12.2A21/PER/927-22/P/E26/WG 6/1FB T20	Frosted	A21 (A21)	461961	14A19/LED/827/FR/P/ND 4/2FB	Frosted	A19 (A19)
479485	16A21/PER/927-22/P/E26/WG 6/1FB T20	Frosted	A21 (A21)	542950	14A19/LED/827/FR/P/ND 4/4FB	Frosted	A19 (A19)
550475	12.2A21/PER/927/P/E26/DIM 6/1FB T20	Frosted	A21 (A21)	463000	10A19/LED/850/FR/P/ND 4/2FB	Frosted	A19 (A19)
550483	12.2A21/PER/930/P/E26/DIM 6/1FB T20	Frosted	A21 (A21)	542968	10A19/LED/850/FR/P/ND 4/4FB	Frosted	A19 (A19)
547091	12.2A21/PER/940/P/E26/DIM 6/1FB T20	Frosted	A21 (A21)	548248	12.5A19/LED/850/FR/P/ND 4/2FB	Frosted	A19 (A19)
550491	12.2A21/PER/950/P/E26/DIM 6/1FB T20	Frosted	A21 (A21)	542976	12.5A19/LED/850/FR/P/ND 4/4FB	Frosted	A19 (A19)
550509	16A21/PER/927/P/E26/DIM 6/1FB T20	Frosted	A21 (A21)	549485	5A19/PER/927-922/CL/G/E26/WGX 1FB T20	Clear	A19 (A19)
550517	16A21/PER/930/P/E26/DIM 6/1FB T20	Frosted	A21 (A21)	549493	8A19/PER/927-922/CL/G/E26/WGX 1FB T20	Clear	A19 (A19)
547125	16A21/PER/940/P/E26/DIM 6/1FB T20	Frosted	A21 (A21)	543116		-	A19 (A19)
550525	16A21/PER/950/P/E26/DIM 6/1FB T20	Frosted	A21 (A21)	545897	8.8A19/PER/940/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
554469	16.6A21/LED/927/P/E26/ND 6/1FB T20	Frosted	A21 (A21)	550400	5A19/PER/927/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
538322	9.5A19/AMB/827-822/DIM 120V 2PK 4/2	Frosted	A19 (A19)	550418	5A19/PER/930/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
479428	5A19/PER/927-22/P/E26/WG 6/1FB T20	Frosted	A19 (A19)	547042	5A19/PER/940/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
479444	8.8A19/PER/927-22/P/E26/WG 6/1FB T20	Frosted	A19 (A19)	550426	5A19/PER/950/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
477612	6A19/PER/850/CL/G/DIM 4/2BC	Clear	A19 (A19)	550434	8.8A19/PER/927/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
548214	6.5A19/LED/827/FR/P/ND 4/2FB	Frosted	A19 (A19)	550442	8.8A19/PER/930/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
461145	6.5A19/LED/827/FR/P/ND 4/4FB	Frosted	A19 (A19)	550459	8.8A19/PER/950/P/E26/DIM 6/1FB T20	Frosted	A19 (A19)
548222	10A19/LED/827/FR/P/ND 4/2FB	Frosted	A19 (A19)	554428	8.8A19/LED/927/P/E26/ND 6/1FB T20	Frosted	A19 (A19)
461129	10A19/LED/827/FR/P/ND 4/4FB	Frosted	A19 (A19)	554444	8.8A19/LED/950/P/E26/ND 6/1FB T20	Frosted	A19 (A19)
469205	10A19/LED/827/FR/P/ND 4/6FB	Frosted	A19 (A19)	549220	5A19/PER/950/CL/G/E26/DIM 1FB T20	Clear	A19 (A19)
462184	5.5A19/LED/850/FR/P/ND 4/2FB	Frosted	A19 (A19)	549238		Clear	A19 (A19)

Temperature

Order Code	Full Product Name	T-Case Maximum (Nom)	Order Code	Full Product Name	T-Case Maximum (Nom)
466565	BC8A19/AMB/827/ND D2D 120V 4/1	70 °C	550491	12.2A21/PER/950/P/E26/DIM 6/1FB T20	90 °C
465187	BC10A19/AMB/927/DIM 120V 4/1	85 °C	550509	16A21/PER/927/P/E26/DIM 6/1FB T20	90 °C
531798	9A19/LED/927/P/E26/ND 4/4FB T20	75 °C	550517	16A21/PER/930/P/E26/DIM 6/1FB T20	90 °C
531806	9A19/LED/950/P/E26/ND 4/4FB T20	75 °C	547125	16A21/PER/940/P/E26/DIM 6/1FB T20	90 °C
531772	18A21/LED/927/P/E26/ND 4/2FB T20	75 °C	550525	16A21/PER/950/P/E26/DIM 6/1FB T20	90 °C
531764	18A21/LED/950/P/E26/ND 4/2FB T20	75 °C	554469	16.6A21/LED/927/P/E26/ND 6/1FB T20	100 °C
479469	12.2A21/PER/927-22/P/E26/WG 6/1FB T20	75 °C	538322	9.5A19/AMB/827-822/DIM 120V 2PK 4/2	85 °C
479485	16A21/PER/927-22/P/E26/WG 6/1FB T20	85 °C	479428	5A19/PER/927-22/P/E26/WG 6/1FB T20	65 °C
550475	12.2A21/PER/927/P/E26/DIM 6/1FB T20	90 °C	479444	8.8A19/PER/927-22/P/E26/WG 6/1FB T20	80 °C
550483	12.2A21/PER/930/P/E26/DIM 6/1FB T20	90 °C	477612	6A19/PER/850/CL/G/DIM 4/2BC	35 °C
547091	12.2A21/PER/940/P/E26/DIM 6/1FB T20	90 °C	548214	6.5A19/LED/827/FR/P/ND 4/2FB	65 °C