



T&B®

Liquidtight Flexible Cord & Cable Fittings

T&B Catalog Number:

UPC Number: 2547
 Status: 78621002547
 Description: Active

Liquidtight Strain Relief Cord Connector, 1 Inch, Straight, Cord Range 0.875 to 0.985 Inch, Die Cast Zinc

Application

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).
 Meets Coast Guard CG293

General

Material Die Cast Zinc

Dimension Information

Hub Size (inches)	1
Dimension A (inches)	1 11/16
Dimension B (inches)	1 7/8
Dimension C (inches)	9/16
Cord Range (inches)	.875-.985
Throat Diameter (inches)	63/64

Specifications

3dmodel	Available on Website
Temperature Rating	105 C

Packaging

T&B Inner Pack	10
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	29.19 lbs. per 100

Application Support

Product Overview	Available on Website
Specifications	Available on Website
Portable Cord Selection Table	Available on Website

Notes

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
 E 13938