



## Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

UPC Number: 5333GR  
Status: 78621089999  
Description: Active

3/4 Inch Steel External Bonding Liquidtight Insulated Connector Flexible Metal Conduit Fitting, Straight, With Revolver Lug, With Tin Plated Copper Alloy Lug for Awg #14 to #2 Ground Wire, for Use In Wet Locations, 25 Pieces

### Features

Ability to install quickly with low torque effort

### Application

To positively bond conduit to box or enclosure

### General

|                     |                                      |
|---------------------|--------------------------------------|
| Trade Size (inches) | 3/4                                  |
| Material            | Steel                                |
| Finish              | Electro Zinc Plated/Chromate Coating |
| Ground Wire         | 14-4                                 |

### Dimension Information

|                      |         |
|----------------------|---------|
| Dimension A (inches) | 1 21/32 |
| Dimension B (inches) | 1 5/8   |
| Dimension C (inches) | 9/16    |

### Specifications

|         |                      |
|---------|----------------------|
| 3dmodel | Available on Website |
|---------|----------------------|

### Packaging

|                    |                 |
|--------------------|-----------------|
| Package in Units   | 25              |
| T&B Sold in UOM    | Each            |
| T&B Weight Per UOM | 26 lbs. per 100 |

### Application Support

|                    |            |
|--------------------|------------|
| T&B Sales Drawings | wsd-001319 |
|--------------------|------------|

### Certifications

|                 |     |
|-----------------|-----|
| RoHS Compliance | Yes |
|-----------------|-----|

### Certifications



File Nbr:  
E 3060

For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321

Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)