



Thin-Wall Heat-Shrinkable Tubing

T&B Catalog Number:

CPO375-0-6

UPC Number:

78621085169

Status:

Active

Description:

Thin-Wall Heat-Shrinkable Tubing for Cable Range 12 - 6 AWG, Expanded Dia. 3/8, Length 6 in., rated for 600V, 125 degrees C, Material: Cross-linked polyolefin - Non-lined, Black

Features

Flame-retardant, cross-linked polyolefin.

Meets UL 224, 125°C; CSA 22.2 No. 198.1, 125°C; MIL-DTL-23053/5 Class 1&2; AMS 3636 & 3637; DEF STAN 59-97, Issue 3, Type 2a

General

| | |
|-------------------|-------------------------------------|
| Style | CPO Series Non-Lined, 6 in. lengths |
| Color | Black |
| Temperature Range | -55°C - 135°C |
| Shrink Ratio | 2:1 |

Dimension Information

| | |
|---------------------------------|------------|
| Minimum Expanded I.D. (inches) | 0.375 |
| Maximum Recovered I.D. (inches) | 0.187 |
| Nominal Recovered Wall (inches) | 0.025 |
| Cable Range | 12 - 6 AWG |
| Standard Length (inches) | 6 |

Specifications

| | |
|--------------------|-------|
| Shrink Temperature | 120°C |
|--------------------|-------|

Packaging

| | |
|--------------------|--------------------|
| T&B Order Multiple | 20 |
| T&B Inner Pack | 20 |
| Package in Units | 200 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 8.75 lbs. per 1000 |

Application Support

| | |
|----------------|----------------------|
| MSDS Number | msds-0020-tb2 |
| Specifications | Available on Website |
| Overview | Available on Website |

Notes

Order multiple is standard package.

Custom colors available. Contact Customer Service.

Certifications

| | |
|-----------------|-----|
| RoHS Compliance | Yes |
|-----------------|-----|

Certifications



For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com