Thomas&Betts



Motor Lead Disconnect **T&B Catalog Number:**

UPC Number: Status: **Description:**

MD350F-4 78620989324 Active

KUBE Female Copper Motor Pigtail Disconnect for Wire Size 350 kcmil, Body Size 4, Die Color Red Features

- B -A

С

F

	Fast, snap-together assembly offers maximum la- bor savings. Not need for nuts, bolts and washers or insulating tape - simply slide on reusable boot.
	Quick disconnect - no knife cutting of melted tape, eliminating the risk of accidental cutting of wire in- sulation, resulting motor downtime and installer ex- posure. Meets or exceeds electrical and mechanical performance of bolted commections.
	Female disconnects equipped with beryllium cop- per louvered contact bands for dependable connec-
Conoral	tions.
General	
Style	Female
Material	Copper
Finish	Tin-Plated
Wire Size	350 kcmil
Die Color	Red
Die Code	71H
Body Size	4
Boot Insulation	MDBOOT4
Dimension Information	
A (inches)	1.25
B (inches)	1.25
C (inches)	2.89
D (inches)	2.69
E (inches)	1.25
F (inches)	.813
Specifications	
Voltage Rating	600V
Tooling	
Application Tools	TBM6, TBM6S, TBM5, TBM5S, TBM8, TBM8S
Packaging	
T&B Inner Pack	3
Package in Units	15
T&B Sold in UOM	Each
T&B Weight Per UOM	51 lbs. per 100
Application Support	
T&B Sales Drawings	wsd-000392
Notes	
	Always use the same body size when selecting
	male and female disconnects. Use insulating boots



matching the disconnect body size. To protect the connection from moisture and dirt, use sealing compound catalog number MDBOOT-SEAL.

Certifications





File Nbr: Y

U

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com